		WATER W	ELL RECC	ORD Fo	rm WV	/C-5 K	SA 82a-12	12		
1 LOCATION OF WATE	ER WELL:	FRACTION	NIE	CITY		TON NUMBER	1 -	P NUMBER	RANGE	
Sedgwick  Distance and direction from	om pograst town or situ	NE 1/4	NE 1/4		1/4	23	<u> </u> T 2	7 s	R 2	W E/W
218 N. Kenne	•	Wichita, Ka		ulty?						
2 WATER WELL		L CONSTRU								***
RR#,ST. ADDRESS		W. 21st N.						Board of Agric	culture, Division of	Water Resource
CITY,	STATE: Wich	ita, Kansas			ZII	P CODE:		Application Num	ber:	
3 LOCATE WELL'S LO	OCATION 4	DEPTH OF COMP	LETED WELL:	120	ft.		ELEVATION:			
WITH AN "X" IN SE	CTION BOX: Dep	oth of groundwater	Encountered:		ft.			ft.		ft.
	WE	ELL'S STATIC WA	TER LEVEL	30	T. BELO	W LAND SU	JRFACE MEAS	URED ON mo/d	ay/yr: <b>9</b> /4	1/15
NW -	NE	Pur	np test data:	Well water	was		ft. after	hours	of pumping @	gpm
w W	·	Est. Yield:	gpm	Well wate	r was		ft. after	hours	of pumping @	gpm
		ore Hole Diameter		in.	to $1$	<b>20</b> ft.	and	in.	to	ft.
sw		LL WATER TO B  Domestic 3.		Public wate	r supply '	7. Lawn a	ind garden onl	9. Dewaterir	'9	ection well
	1			Oil field wat				10. Monitorin		specify below
S		as a chemical/bacter				YES	NO		hat mo/day/yr	
		omitted				Was V	Vater Well Disir	fected? (	YES	NO
5 TYPE OF CAS	SING USED: 3. RPM (SR	5. Wrought	Iron 7.	Fiberglass	9. Ot	her (Specify	below) CA	SING JOINTS: (	Glued	Threaded
2. PVC	3. KFW (3K	6. Asbestos	-Cement 8.	Concrete tile	SDI	R-26			Welded	Clamped
Blank casing diamete	_	in. to	40 ft.,	Dia.	in.	to	ft.,	Dia. j	n. to	ft.
Casing height above	_	12 <sub>in</sub>	,			os. / ft.			-	
TYPE OF SCREEN		,	V	veignt: 2		os. / π.	vvaii tr	nickness or gaug	e No214	•
1	3. Stainless Steel	5. Fiberglass	(7. F	PVC	9. Al	3S	11. O	ther (specify)		
2. Brass	4. Galvanized	6. Concrete T	ile 8. f	RMP (SR)	10. A	sbestos-Cer	nent 12. N	one used (open l	nole)	
SCREEN OR PERFO	DRATION OPENING	SS ARE:								
1. Continuous slot	t 3. Mill slo	ot 5. 0	Sauzed wrappe	ed	7. <b>To</b> i	rch cut	9. <b>Dril</b>	led holes	11. None (	open hole)
2. Louvered shutte	er 4. Key pu	ınched 6. V	Vire wrapped		(8. Sa)	w cut	10. Oth	er (specify)		
SCREEN - PERFORA	• •	From	<b>40</b> ft.	to	120					<b>.</b> .
30KELIV-FERFOR	ATION INTERVAL	From	ft.	to	120	ft.,	From	ft.	to	ft.
CBAVEL BA	CK INTERVALS:		24 ft.	to	120	ft.,	From	ft.	to .	ft.
GRAVEL PA	ICK INTERVALS.	From			120	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug										lug
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to What is the nearest source of possible contamination:								ft.		
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/							Gas well			
2. Sewer lines	5. Cess P	ool 8.	Sewage lago	on 11	. Fuel stor	age	14. Aband	lon water well	16. Other (s	pecify below)
₩atertight sewer	er line 6. Seepag	ge pit 9.	Feed yard	12	Fertilizer	storage				
Direction from well?	North						How m	any feet? 20 f		
From To	<u> </u>	<u>LITHOLOGIC</u>	LOG		From	То		LITHOLO	GIC LOG	
0 3	topsoil									
3 26 26 120	clay grey shale							••••		
20 120	grey shale									<del></del>
					-					
-										
						-				
	<del> </del>									
7 Contractor's or	Landowner's Certific	ation: This water:	well was 1	onetruotad	) 0	onstructed	l or 3	nlugged ·	inder my juriodia	tion and
<b>一</b>		9/4/2015	_	onstructed					ınder my jurisdic	anu
was completed on						-	knowledge and		-01-	
Kansas Water Well	l Contractor's Licens	e No. 236	Th	ns water well	record was	s completed	on (mo/day/yea		2015	
under the business	name of Harp V	Well and Pun	ip Service		by (sig	nature)	$\mathcal{T}$	odd S.	. Hart	)