State WATER WELL RECORD Form WWC-5 Division of Water Original Record Correction Change in Well Use Resources App. No. Well ID Fraction 1 LOCATION OF WATER WELL: Section Number | Township Number | Range Number SEXSW NEXS W 23 T27 S R 2 DE NW Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: Address: 199 N Jawalwa ZP: 67235 City: 3 LOCATE WELL 5 Latitude: 37. 682623 (decimal degrees)
Longitude: 97. 5107 44 (decimal degrees) 4 DEPTH OF COMPLETED WELL: 120 ft. WITH "X" IN Depth(s) Groundwater Encountered: 1) ft. SECTION BOX: 2) ft. 3) ft., or 4) ☐ Dry Well WELL'S STATIC WATER LEVEL: ft. Datum: ☐ WGS 84 M NAD 83 ☐ NAD 27 Source for Latitude/Longitude: GPS (unit make/model:) - NW - -(WAAS enabled? ☐ Yes ☐ No) Pump test data: Well water was ft. ☐ Land Survey ☐ Topographic Map after..... hours pumping gpm Online Mapper: Well water was ft. -- SW --- SE - -6 Elevation:ft. Ground Level TOC Bore Hole Diameter: .1.2... in. to ft. and Other -1 mile in. to ft. 7 WELL WATER TO BE USED AS: 1. Domestic: 5. Public Water Supply: well ID 10. Oil Field Water Supply: lease ☐ Household 6. Dewatering: how many wells? 11. Test Hole: well ID Lawn & Garden ☐ Cased ☐ Uncased ☐ Geotechnical 7. Aquifer Recharge: well ID ☐ Livestock 8. Monitoring: well ID 12. Geothermal: how many bores? 2. Irrigation 9. Environmental Remediation: well ID 3. Feedlot ☐ Air Sparge ☐ Soil Vapor Extraction 4. Industrial ☐ Recovery □ Injection 13. Other (specify): Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes 🛛 No If yes, date sample was submitted: Water well disinfected?

Yes □ No 8 TYPE OF CASING USED: Steel NPVC Other CASING JOINTS: NGlued Clamped Welded Threaded Casing diameter fi. biameter in. to fi. biameter in. to fi. Casing height above land surface in. Weight 60 lbs/ft. Wall thickness or gauge No. 65 lbs/ft. TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel PVC None used (open hole) ☐ Fiberglass Other (Specify) ☐ Brass ☐ Galvanized Steel ☐ Concrete tile SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify)

Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)

SCREEN-PERFORATED INTERVALS: From 4.0. ft. to 12.0. ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 2.4. ft. to 12.0. ft., From ft. to ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other

Grout Intervals: From 4.5 ft. o 2.4 ft. From ft. to ft. Nearest source of possible contamination: Septic Tank ☐ Lateral Lines ☐ Pit Privy ☐ Livestock Pens ☐ Insecticide Storage Cess Pool ☐ Sewer Lines ☐ Sewage Lagoon ☐ Fuel Storage Abandoned Water Well Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well Other (Specify) Distance from well? Direction from well? 10 FROM LITHO. LOG (cont.) or PLUGGING INTERVALS LITHOLOGIC LOG FROM TO Notes:

INSTRUCTIONS: Send one copy to WATER WELL OWNER and retain one copy for your records. Submit fee of \$5.00 for each constructed well along with one (white) copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone (785) 296-3565.