County:	Fraction:	!	Sec	T	S	R	
CORRECTION(S) to WATER WELL	COMPLETION RECORD	Form	WWC-5	(to rectify lac	king or	incorrect	t information)
Owner:							
If location corrected, was listed as:			Location	changed to:			
Section-Township-Range:		_					
Fraction (¼ calls):							
Other changes: Initial statements:							
Changed to:							
Comments:							
Verification method:			·				
			Initi	ials:	_ Date:		
, =	rvey, Data Resources Library, 1 th & Environment, Bureau of Wa						6612-1367

(rev 01/26/2018)

WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick SE SE 1/4 1/4 36 Т 28 s 2W E/W Distance and direction from nearest town or city street address of well if located within city? 2317 S. Limuel Circle Wichita, Kansas NANK, Paul WATER WELL OWNER: Board of Agriculture, Division of Water Resource 2317 S. Limuel Circle RR#,ST. ADDRESS,BOX #: Wichita, Kansas CITY, STATE: ZIP CODE Application Number: 100 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ft. **ELEVATION:** WITH AN "X" IN SECTION BOX: ft. ft. Depth of groundwater Encountered: ft. WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm NW NE Est. Yield: apm Well water was ft. after hours of pumping @ gpm Ī Bore Hole Diameter 12 to 100 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 1. Domestic 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) Was Water Well Disinfected? (YES) submitted 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: C Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 Blank casing diameter 60 ft., Dia. ft., Dia. in. to to ft. in. to 12 2.35 Casing height above land surface: in., Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 2 Brass 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) Galvanized 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 1. Continuous slot 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 100 60 ft. From to ft. From to ft. ft. to From ft., From ft ft to **GRAVEL PACK INTERVALS:** 24 ft. 100 ta From ft., From to ft. ft. From to ft., From to ft. **GROUT MATERIALS** 6 Other 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 24 From ft. to ft.. From ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 3. Watertight sewer line 6. West 9. Feed yard 12. Fertilizer storage 6. Seepage pit How many feet? 50 ft. plus From LITHOLOGIC LOG From Τo To LITHOLOGIC LOG topsoil 55 3 clay 55 70 medium sand 70 85 clay 85 <u> 100</u> gray shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and plugged 3-30-16 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4/1/16 by (signature) under the business name of Harp Well and Pump Service Todd S. Harp