			WATER	WELL RE	ECORD	Form W	WC-5	(SA 82a-12	212		
1 LOCATIO	N OF WATE	R WELL:	FRACTION				SECTION NUMBER		HIP NUMBER	RANGE NUMBER	
Sedgy	wick		SW 1	1/4 SE	1/4 SW	/ 1/4	11	T	27 s	R 2W	E/W
		m nearest town or cit	-		•						
		stone Ct.		ichita, Ka	nsas						
	ER WELL (NTAGE, Jes						Board of Agr	iculture, Division of Wa	ster Persurce
RR#,S1.	ADDRESS		5 N. Blackst chita, Kansa						_		ner resource
			, 				ZIP CODE:		Application Nur	mber:	
	E WELL'S LC N "X" IN SEC	TION BOX:	DEPTH OF CO					ELEVATION:			
l. —	N N		epth of groundw				ft.		ft.		ft.
			WELL'S STATIC				OW LAND S	URFACE MEAS	SURED ON mo/	day/yr: 4/26/	16
	NW	NE-		Pump test da	-	vater was		ft. after		s of pumping @	gpm
W Wile		_	Est. Yield:	gpm eter 12	_	vater was	60	ft. after		s of pumping @	gpm
5 "	:		Bore Hole Diam VELL WATER TO			to	68 fi	t. and	in.	to	ft.
	sw -	2-	1. Domestic	3. Feedlot		vater supply	7. Lawn	and garden or	9. Dewateri	•	
	×	1	2. Irrigation	4. Industria			ly 8. Air co		10. Monitori	12. Other (Spe ng well	city below)
'	S	4	Was a chemical/ba	acteriological sa			-	NO	; If yes,	what mo/day/yr wa	-
<u> </u>			submitted				Was	Water Well Disi	nfected?	YES N)
191		SING USED:	5. Wrou	ight Iron	7. Fiberglas	ss 9. 0	Other (Specif	y below) CA	SING JOINTS:	Glued	Threaded
1	. Steel	3. RPM (S	•	stos-Cement	8. Concrete	s tile SI	DR-26			Welded	Clamped
	. PVC	> 4. ABS er 5				_	4-	£ı.	D:-		
	ing diamete	_	in. to		•	in.	to	ft.,	Dia.	in. to	ft.
1 -	-	land surface:	12 in.	•	Weight:	2.35	lbs. / ft.	Wall	thickness or gau	ge No214	
=		OR PERFORATIO		acc (7. PVC	Q	ABS	11 (Other (spe c ify)		
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)							Asbestos-Ce		None used (open	hole)	
				ic riic	O. 1400 (O14	, 10.	Aspesios-Ce	1116111 12.1	tone daca (open	noie)	
1		RATION OPENIN 3. Mill :		5 Courad w		7 T	anah aut	0 D -	illed holes	44 None / on	en hole)
	nuous siot		siot .	5. Gauzed w	• •		orch cut			11. None (op	en noie)
2. Louve	ered shutte	r 4. Key	punched	6. Wire wrap	ped	(8. S	aw cut	10. Ot	her (specify)		
SCREEN -	PERFORA	TION INTERVAL	. From	48	ft.	to 68	ft.,	From	ft.	to	ft.
			From		ft.	to	ft.,	From	ft.	to	ft.
GI	RAVEL PA	CK INTERVALS:	From	24	ft.	to 68	ft.,	From	ft.	to	ft.
			From		ft.	to	ft.,	From	ft.	to	ft.
6 GROL	JT MATERI	ALS: 1 Non	t coment	2 Com	ant Crout						
Grout Intervals: 1. Neat cement 2. Cement Grout Grout Intervals: From 4 ft. to 24 ft., From							o. Bontonice Bontonice Hote Plug			₽ ft.	
What is the nearest source of possible contamination:						•					
1. Septic tank 4. Lateral lines 7. Pit privy						10. Livesto	ck pens	13. Inse d	13. Insecticide storage 15. Oil well/Gas well		
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other									16. Other (spe	cify below)	
3. Water	tight sewe	r line 6. Seep	age pit	9. Feed yaı	rd	12. Fertiliz	er storage				
Direction f		North					. ,	How r	nany feet? 50		
From	То		LITHOLOG	<u> GIC LOG</u>		From	<u>To</u>	ļ	LITHOLO	OGIC LOG	
0	3	topsoil					-				
3	25	clay					-				
25 45	45 65	fine sand medium san									
65	68	clay	<u> </u>				1				
- V2/											**************************************
 								ļ			
			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,					<u> </u>			
\vdash							<u> </u>				-
7 Cont	ractor's or I	andowner's Certi	ification: This wa	ater well was 1	1. Construct	ed) 2 r	econstructe	d or 3,	plugged	under my juńsdictio	n and
		(mo/day/year)	4/26/1					knowledge and			
	•			-			_	-		- H C	
Kansas \	water Well	Contractor's Lice	nse No. 236		ı nıs water	well record w	as completed	d on (mo/day/ye	,	7/16	
under the	e business	name of Harp	Well and P	ump Serv	rice	by (s	signature)	7	odds	. Harp	
L									2 2000 0	. , coor p	