		WATER	WELL REC	ORD F	orm WW	/C-5 K	SA 82a-12	212		
1 LOCATION OF WAT	ER WELL:	FRACTION				ION NUMBER		IIP NUMBER	RANGE NU	MBER
Sedgwick		SE ·	1/4 NE 1	/4 SW	1/4	11	Т :	27 s	R 2W	E/W
Distance and direction f	rom nearest town or	city street address o	f well if located within	n city?						
1615 Obsidi	an	Wiel	hita, Kansas							
2 WATER WELL	OWNER: KI	LAUSMEYE	R CONSTR	UCTION						
RR#,ST. ADDRES		008 W York						Board of Agric	culture, Division of Wa	ter Resource
CITY	, STATE: W	ichita, Kansa	ıs			P CODE:		Application Num	ber:	
3 LOCATE WELL'S	LOCATION	4 DEPTH OF CO	OMPLETED WEL	.L: 70	ft.		ELEVATION:			
WITH AN "X" IN S		Depth of groundw	ater Encountered	d:	ft.			ft.		ft.
		WELL'S STATIC	WATER LEVEL	32	FT. BELO	W LAND SU	RFACE MEAS	SURED ON mo/d	ay/yr: 7/9/1	6
	NE		Pump test data:	Well water	er was		ft. after	hours	of pumping @	gpm
<u>o</u>	'	Est. Yield:	gpm	Well water	er was		ft. after	hours	of pumping @	gpm
w N	E	Bore Hole Diam	eter 12	in.	to 7	0 ft.	and	in.	to	ft.
l- I ∵ X	-		O BE USED AS:			<u> </u>		9. Dewaterir	ng 11. Inject	ion well
1. Domestic 3. Feedlot 5. Public water supply 7 Lawn and garden only 12. Other (Specify below)										
	2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/bacterological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample									
S	'	submitted	acteriological samp	ic sobilimica to Di	sportment:		ater Well Disi		YES N	
5 TYPE OF CA	ASING USED:	5 \M/ro/	ught Iron	7. Fiberglass	9. Ot	her (Specify	below) CA	ASING JOINTS: C	Glued	Threaded
1. Steel	3. RPM	(SR)	-	•	cDi	R-26	,		Welded	Clamped
2. PVC	A. ABS	6. Asbe	estos-Cement	8. Concrete tile	9 301	X-20				
Blank casing diame	eter 5	in. to	50 ft.,	Dia.	in.	to	ft.,	Dia. i	n, to	ft.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)										
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
1. Continuous si	ot 3. Mil	ll slot	5. Gauzed wrap	ped	7. To	rch cut	9. Dr	illed holes	11. None (op	en hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)										
SCREEN - PERFOR	RATION INTERVA	AL From	50 ft.	. to	70	ft.,	From	ft.	to	ft.
From			ft	to		ft.,	From	ft.	to	ft.
GRAVEL F	ACK INTERVALS	S: From	24 ft.	to	70	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATE	RIALS: 1. Ne	eat cement	2. Cemer	t Grout	3	Bentonite		Other bent	onite hole plu	
Sentence Sen										ft.
What is the nearest	source of possible	e contamination:		10	. Livestoc	k nene		atioido atazana	15 Oil wall/Ga	a wall
1. Septic tank	4. Lat	eral lines	7. Pit privy			•		cticide storage	15. Oil well/Ga	
2. Sewer lines	5. Ce s	ss Pool	8. Sewage lag		1. Fuel sto	_	14. Aban	idon water well	io. Other (spe	city below;
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage										
Direction from well	South	LITUOLO	0101.00		F	T = \	How r	many feet? 30 f		
From To	1,	LITHOLO	GIC LOG		From	То		LITHOLO	GIC LOG	
3 35	topsoil clay									
35 45	fine sand									
45 70	medium sa	ınd								
										
										
						<u> </u>				
7 Contractor's o	r Landowner's Ce	ertification: This w	ater well was 1.0	constructed) 2. re	constructed	or 3.	plugged	under my jurisdictio	n and

was completed on (mo/day/year)

7/9/16

And this record is true to the best of my knowledge and belief.

This water well record was completed on (mo/day/year)

7/11/16

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp