WATER WEI	L RECORD F	orm WW	/C-5 K	SA 82a-1212					
1 LOCATION OF WATER WELL: FRACTION			ION NUMBE	TOWNSHIP NU	MBER	RANGE NUMBER			
Sedgwick SE 1/4	SE 1/4 NE 1/4 SW		11 T		S R 2W EA		E/W		
Distance and direction from nearest town or city street address of well if	ocated within city?								
1615 Obsidian Wichita,	Kansas								
2 WATER WELL OWNER: KLAUSMEYER CO	ONSTRUCTION								
	Board of Ac						r Resource		
CITY, STATE: Wichita, Kansas	CITY, STATE: Wichita, Kansas ZIP CODE:					Application Number:			
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLE	TED WELL: 70			ELEVATION:					
WITH AN "X" IN SECTION BOX:		ft.			ft.		ft.		
N Depth of groundwater E						= 10.14 A			
WELL'S STATIC WATE	ER LEVEL 32	FT. BELO	W LAND S	JRFACE MEASURE		• •)		
1 1 "" 1 "- 1 1	test data: Well wat	er was		ft. after		of pumping @	gpm		
Est. Yield: Bore Hole Diameter	gpm Well wat			ft. after	hours	s of pumping @	gpm		
	12 in.	to 7	0 ft.	and	in.	to	ft.		
─ WELL WATER TO BE				-	Dewateri	ng 11. Injectio	n well		
				and garden only		12. Other (Spec	ify below)		
	dustrial 6. Oil field w				D. Monitorii	ıg well what mo/day/yr was	camala		
S Was a chemical/bacteriol submitted	ogical sample submitted to D	epartment?	YES	NO Water Well Disinfect		YES NO	Sample		
						\succ			
TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Inc.	on 7. Fiberglass	9. Ot	her (Specify	below) CASING	3 JOINTS: (readed		
C Ashantan C	Cement 8. Concrete til	s SDI	R-26			Welded C	lamped		
2. FVC 4. ABS									
Blank casing diameter 5 in. to 25	5 ft., Dia.	in.	to	ft., Dia		in. to	ft.		
Casing height above land surface: 12 in.,	Weight:	2.35 ib	s. / ft.	Wall thick	ness or gau	ge No214			
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
	urad wranad	7 To	rch cut	0 Drillad	holes	11 None / one	n hole)		
1. Continuous slot 3. Mill slot 5. Gauzed wrapped					9. Drilled holes 11. None (open hole)				
2. Louvered shutter 4. Key punched 6. Wi	re wrapped	8. Sa	w cut	10. Other (specify)				
SCREEN - PERFORATION INTERVAL From	25 ft. to	40	ft.,	From	ft.	to	ft.		
From	ft. to		ft.,	From	ft.	to	ft.		
	24 ft. to	40	•	_					
GRAVEL PACK INTERVALS: From		40	ft.,	From	ft.	to	ft.		
From	ft. to		ft.,	From	ft.	to	ft.		
6 GROUT MATERIALS: 1. Neat cement	2. Cement Grout	3	. Bentonite	Ot	ner bent	onite hole plug			
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to						ft.			
What is the nearest source of possible contamination:				,					
1. Septic tank 4. Lateral lines 7. Pit privy 10. L			k pens	• • • • • • • • • • • • • • • • • • • •					
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below							ify below)		
Watertight sewer line 6. Seepage pit 9. F	eed yard 1	2. Fertilizer	rstorage						
Direction from well? North	•			How many	feet? 40	ft. plus			
From To LITHOLOGIC	LOG	From	То			OGIC LOG			
		110111	1	-		010 200			
0 3 topsoil 3 8 clay									
8 24 fine sand									
24 40 medium sand			İ		-				
24 40 meanum sano									
					-				
7 Contractor's or Landowner's Certification: This water w	ell was 1. constructed) 2 re	constructe	d or 3. plu	gged	under my jurisdiction	and		
71011		_				,,			
was completed on (mo/day/year) //8/16	and this record	is tiue to the	e pest of my	knowledge and beli	ei.				
Kansas Water Well Contractor's License No. 236									
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp									
under the business name of Harp Well and Pum				d on (mo/day/year)		1/16			