Form WWC-5 WATER WELL RECORD KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER SWSedgwick 1/4 NE 1/4 1/4 11 T 27 s 2WΕ/W Distance and direction from nearest town or city street address of well if located within city? 1603 Obsidian Wichita, Kansas WATER WELL OWNER: KLAYSMEYER CONSTRUCTION Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 10008 W. York CITY, STATE: Wichita, Kansas ZIP CODE Application Number: LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 68 ft. **ELEVATION** WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. 25 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/vr: 11/10/16 Pump test data: Well water was ft. after hours of pumping @ NW NE apm Est. Yield: Well water was ft. after hours of pumping @ gpm Ξ Bore Hole Diameter 12 to 68 ft. WELL WATER TO BE USED AS: 11. Injection well sw 9. Dewatering 5. Public water supply 7. Lawn and garden only SE 3. Feedlot 1. Domestic 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation ; If yes, what mo/day/yr was sample (NO) Was a chemical/bacteriological sample submitted to Department? (YES) submitted Was Water Well Disinfected? TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 48 Dia. to ft., in. to ft., Dia. in to ft 12 2.35 Casing height above land surface: in.. Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL 7. PVC 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 2 Brass 4. Galvanized Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 48 68 From to ft. From to ft. ft. From to ft.. From ft to ft. **GRAVEL PACK INTERVALS:** 24 ft From to 68 ft., From to ft ft. From to ft.. From ft. ft. **GROUT MATERIALS** Other 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 4 ft. 24 ft., From ft. to ft., From What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3 Watertight sewer line How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG From Τo From. Τо LITHOLOGIC LOG topsoil 3 24 clay 24 45 fine sand 45 medium sand 68 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and

Contractor's or Landowner's Certification: This water well was 1. Constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 11/10/2016 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 11/15/2016

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp