Form WWC-5 WATER WELL RECORD KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NE 1/4 SE 1/4 1/4 26 Т 27 S R 2W E/W Distance and direction from nearest town or city street address of well if located within city? 14402 Valley Hi Rd. Wichita, Kansas BLUE CUSTOM HOMES LLC WATER WELL OWNER: Board of Agriculture, Division of Water Resource 106 S. Breezy Pointe Circle RR#,ST. ADDRESS,BOX #: Wichita, Kansas CITY, STATE: ZIP CODE Application Number: 125 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ELEVATION: WITH AN "X" IN SECTION BOX: ft. Depth of groundwater Encountered: ft. ft WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 11/30/16 Pump test data: Well water was ft. after NW NE apm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm ⋝ ٧ Bore Hole Diameter 12 to 125 in. ft WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SE SW 1. Domestic 3. Feedlot 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO (YES) submitted Was Water Well Disinfected? TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: (Glued Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 5 40 ft., Dia. in. to in. to ft.. Dia ft in to 12 2.35 Casing height above land surface: in. Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 6. Concrete Tile 8. RMP (\$R) 12. None used (open hole) 2. Brass Galvanized Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 3 Mill slot 7. Torch cut 9 Drilled holes 1 Continuous slot 5. Gauzed wrapped 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 125 From From to ft. ft. to From ft.. From ft to 24 ft. GRAVEL PACK INTERVALS: to 125 ft., From From to ft ft. From to ft., From ft. **GROUT MATERIALS** Other 6 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 4 ft. 24 ft From ft. to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line 10 ft. plus Direction from well? How many feet? From LITHOLOGIC LOG LITHOLOGIC LOG Τо From To 0 <u>topsoil</u> 20 clay 20 27 very fine sand 27 80 gray shale 95 80 red shale 95 125 gray shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 11-30-16 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year)

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb