		WATER W	ELL RECO	RD Fo	orm WV	VC-5 I	KS A 82a-12	12		
1 LOCATION OF WATI	ER WELL:	FRACTION				TION NUMBE		IP NUMBER	RANGE I	
Sedgwick		SE 1/4	NW 1/4		1/4	11	Т 2	27 s	R 2	W E/W
Distance and direction fro		=		ty?						
1985 N. Belli		Wichita, I						····		
2 WATER WELL		SE-SIMPSON,	•					Board of Agri	culture. Division of	Water Beneume
RR#,ST. ADDRESS	RESS,BOX #: 1985 IV. BEIICK Ct.								culture, Division of	Waler Resource
-		chita, Kansas			ZI	P CODE:		Application Nun	nber:	
3 LOCATE WELL'S L WITH AN "X" IN SE		DEPTH OF COMP	PLETED WELL:	70	ft.		ELEVATION:			
WITH AN A IN SE		epth of groundwate	r Encountered:		ft.			ft.		ft.
		VELL'S STATIC WA	ATER LEVEL	30	FT. BELO	W LAND S	URFACE MEAS	URED ON mo/o	lay/yr: 6/1	3/07
NW -	NE	Pu	mp test data:	Well wate	r was		ft. after	hours	of pumping @	gpm
1 1 1		Est. Yield:	gpm	Well wate	r was		ft. after		of pumping @	gpm
W Wile	E 1	Bore Hole Diameter	r 12 ir	n.	to 7	70 f	t, and	in.	to	ft.
		VELL WATER TO E						_ 9. Dewateri	na 11. Inje	ection well
sw	SE	1. Domestic 3.					and garden on	₩	_	specify below)
		_		Oil field wa		8. Air co	nditioning	10. Monitorir	_	
S		Was a chemical/bacte submitted	riological sample su	ubmitted to De	partment?	YES	NO NO		what mo/day/yr	was sample NO
EL TYPE OF CA		autiliteu				was	Water Well Disir		=	
5 TYPE OF CA	SING USED: 3. RPM (S	5. Wrought	Iron 7. f	Fiberglass	9. O	ther (Speci	fy below) CA	SING JOINTS: (Glued	Threaded
2. PVC	> 4. ABS	6. Asbestos	s-Cement 8. (Concrete tile	SDI	R-26			Welded	Clamped
Blank casing diamet	_	in. to	50 ft.,	Dia,			4	Die		
1		10	,	_	in.	to	ft.,	Dia.	in. to	ft.
Casing height above		12 in.,	W	eight: 2	2.35 It	os. / ft.	Wall t	hickness or gaug	ge No214	ļ
TYPE OF SCREEN			7.5	110			44.0	4b (
	3. Stainless Steel	5. Fiberglass	7. P		9. A			ther (specify)		
2. Brass	4. Galvanized	6. Concrete T	ile 8. R	RMP (SR)	10. A	sbestos-Ce	ement 12. N	one used (open	hole)	
SCREEN OR PERF	ORATION OPENIN	NGS ARE:								
1. Continuous slot 3. Mill slot 5. Gauzed wrapped						7. Torch cut 9. Drilled holes 11. None (open hole)				
2. Louvered shutt	er 4. Key p	punched 6. \	Wire wrapped		(8. Sa	w cut	10. Oth	ner (specify)		
SCREEN BEREAR	TION INTERVAL	-	50 ft.	4	70		_			
SCREEN - PERFOR	ATION INTERVAL	=		to .	70	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PA	ACK INTERVALS:	From	24 ft.	to	70	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATER	RIALS: 1. Neat	t cement	2. Cement G	rout	3	3. Bentonit	e	Other bent	onite hole pl	าาฮ
Grout Intervals:	From 4	ft. to	24 ft.,	From	ft.	to	- ft.,	From	ft. to	J
What is the nearest source of possible contamination:										
1. Septic tank 4. Lateral lines 7. Pit privy 10.					. Livestoc	k pens	13, Insect	ticide storage	15. Oil well/	
2. Sewer lines	5. Cess	Pool 8	. Sewage lagoo	n 11	. Fuel sto	rage	14. Abane	don water well	16. Other (s	pecify below)
3. Watertight sew	er line 6. Seepa	age pit 9	. Feed yard	12	. Fertilize	r storage				
Direction from well?	North						How m	any feet? 50 f	t. plus	
From To		LITHOLOGIC	CLOG		From	То		LITHOLO	GIC LOG	
0 3	topsoil					<u> </u>				
3 35	elay						<u> </u>			
35 45	fine sand					ļ	<u> </u>			
45 70	medium san	<u>d</u>				ļ	<u> </u>			
	 	·				<u> </u>	<u> </u>			
-	1					 	 			
	1					 	 		,	
	1						ì			<u></u>
	i			<u> </u>		İ	<u> </u>			
						i	İ			
	<u> </u>									
7 Contractor's or	Landowner's Certif	fication: This water	well was 1.Co	nstructed) 2. re	constructe	ed or 3.	plugged	under my jurisdic	tion and
was completed on		6/13/17	_						, ,	
·						_	knowledge and			
Kansas Water Wel	l Contractor's Licer	nse No. 236	Thi	is water well	record wa	s complete	d on (mo/day/ye	ar) 6/1	6/17	
under the business name of Harp Well and Pump Service by (signature) Todd S. Horp										
			-				- 1	U VVVV J	. ILVUTL	,