WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NE NE 1/4 1/4 23 Ţ 27 S 2W E/W R Distance and direction from nearest town or city street address of well if located within city? 112 N. Kennedy Wichita, Kansas BLUE CUSTOM HOMES LLC WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 106 S. Breezy Pointe Circle CITY, STATE: Wichita, Kansas ZIP CODE: 67235 Application Number: 120 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION ft. **ELEVATION:** WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr. 7/3/17 Pump test data: Well water was MW NE ft. after gpm Est. Yield: map Well water was ft. after hours of pumping @ gpm Ξ 12 Bore Hole Diameter to 120 ín. ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 317 SE 5. Public water supply 7. Lawn and garden only 3. Feedlot 1. Domestic 12. Other (Specify below) 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) submitted Was Water Well Disinfected? YES' TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: C Glued Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) Steel SDR-26 Welded Clamped 8. Concrete tile Asbestos-Cement 2. PVC 4. ABS 5 Blank casing diameter 50 Dia. in. ín, ft.. Dia. to in. to ft. 12 Casing height above land surface: 2.35 in.. Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 3. Stainless Steel 9 ABS 11. Other (specify) 1. Steel 5. Fiberglass 8. RMP (SR) 2. Brass 4. Galvanized 6. Concrete Tile 12. None used (open hole) 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill stot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 4. Key punched 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 50 120 ft. From to ft. From to ft. ft. From to ft., From ft to ft. GRAVEL PACK INTERVALS: 24 fL to 120 From ft., From to ft. From ft. to ft., From ft. ft. **GROUT MATERIALS:** Other 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 24 ft. From ft. to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit West Direction from well? How many feet? 10 ft. plus LITHOLOGIC LOG From To <u>From</u> Τo LITHOLOGIC LOG topsoil 18 clay 18 fine sand 27 120 grey shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and plugged 7/3/17 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/5/17 under the business name of Harp Well and Pump Service by (signature) Todd S. Harb