WATER WELL RECORD Form WWC-5 KSA 82a-1212 SECTION NUMBER FRACTION TOWNSHIP NUMBER LOCATION OF WATER WELL: RANGE NUMBER SE Sedgwick NE 1/4 11 27 2WDistance and direction from nearest town or city street address of well if located within city? 1623 N. Obsidian St. Wichita, Kansas WATER WELL OWNER: KLAUSMEYER CONSTRUCTION Board of Agriculture, Division of Water Resource 10008 W. York RR#,ST. ADDRESS,BOX #: Wichita, Kansas CITY, STATE: ZIP CODE Application Number: 68 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION ft. **ELEVATION:** WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. Ν 28 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was NW ΝE ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm ≌ W Bore Hole Diameter 12 to 35 ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering sw > 5. Public water supply 7. Lawn and garden only SE 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 4. Industrial 6. Oil field water supply 8. Air conditioning 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO YES Was Water Well Disinfected? YES submitted NO 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Clued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded SDR-26 Clamped 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 48 Blank casing diameter Dia. Dia. to in. ft. 12 Casing height above land surface: in. Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9 ABS 11. Other (specify) 3. Stainless Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 48 68 to ft.. From to ft. ft. From to ft., From ft to 24 **GRAVEL PACK INTERVALS:** ft. From to 68 ft., From to ft. ft. From ft., From ft. **GROUT MATERIALS** Other bentonite hole plug 6 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 24 ft., ft. to ft., From ft. What is the nearest source of possible contamination 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2 Sewer lines 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3 Watertight sewer line Direction from well? South How many feet? 50 ft. plus From Τo Τo LITHOLOGIC LOG From LITHOLOGIC LOG topsoil 35 clay 35 40 fine sand 40 medium sand

Contractor's or Landowner's Certification: This water well was 1. Constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 2/8/18 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 2/12/18

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp