WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NWSedgwick SW1/4 NW1/4 1/4 26 27 S 2WE/W Distance and direction from nearest town or city street address of well if located within city? 14605 W. Valley Hi. Wichita, Kansas **BLUE CUSTOM HOMES LLC** WATER WELL OWNER: Board of Agriculture, Division of Water Resource 106 S. Breezy Pointe Circle RR#,ST. ADDRESS,BOX #: ZIP CODE: 67235 Wichita, Kansas CITY, STATE: Application Number: 125 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: **ELEVATION** WITH AN "X" IN SECTION BOX: ft. ft. Depth of groundwater Encountered: ft. WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ qpm NW NE Est. Yield: apm Well water was ft. after hours of pumping @ gpm ≌ Bore Hole Diameter 12 125 and ft WELL WATER TO BE USED AS: 11. injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 1. Domestic 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) YES (YES) NO submitted Was Water Well Disinfected? TYPE OF CASING USED: 5 9. Other (Specify below) CASING JOINTS: Clued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 4. ABS 2. PVC 5 45 Dia. ft., Dia. ft. to ft.. to in. to Blank casing diameter in. 12 2.35 Weight: lbs. / ft. Wall thickness or gauge No. .214 Casing height above land surface: TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 3. Stainless Steel 5. Fiberglass 9. ABS 1 Steel 8. RMP (SR) 12. None used (open hole) 6. Concrete Tile Asbestos-Cement 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 1. Continuous slot 3. Mill slot 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched 45 125 SCREEN - PERFORATION INTERVAL to ft . From ft. From to From to ft., From ft. to 24 **GRAVEL PACK INTERVALS:** ft. to 125 From ft.. From ft. ft. to ft.. From From to ft. Other **GROUT MATERIALS:** 1. Neat cement 2 Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: 4 ft 24 ft. From From ft ft. to ft., From What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 13. Insecticide storage 7. Pit privy 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool 12. Fertilizer storage 9. Feed yard 6. Seepage pit 3. Watertight sewer line Southeast How many feet? 60 ft. plus Direction from well? LITHOLOGIC LOG From LITHOLOGIC LOG From Τo Τо 0 topsoil 26 3 clay fine sand 26 32 32 125 gray shale under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged 2/13/18 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. 2/14/18 Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) by (signature) Todd S. Harb under the business name of Harp Well and Pump Service