	WATER WEL	LL RECORD F	orm WV	VC-5 K	SA 82a-121	2		
1 LOCATION OF WATER WELL:	FRACTION	GIV.	i	TION NUMBER	1		RANGE NU	
Sedgwick		SW 1/4 NW	1/4	13	T 27	7 S	R 2W	E/W
Distance and direction from nearest town or city 13314 W. Lost Creek		ta, Kansas						
	···	ONSTRUCTION				*** ** C.1		
RR#,ST. ADDRESS,BOX #: 1000	8 W. York					Board of Agric	culture, Division of Wa	ter Resource
CITY, STATE: Wicl	hita, Kansas			P CODE:		Application Num	nber:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLE	TED WELL: 10	0 ft.		ELEVATION:			
N De	epth of groundwater Er		ft.			ft.	< 10.0	ft.
	ELL'S STATIC WATE			W LAND SU	RFACE MEASU			
NW NE	Pump Est. Yield:	test data: Well wat gpm Well wa			ft. after ft. after		of pumping @ of pumping @	gpm g p m
₩ X B	Bore Hole Diameter	12 in.	to 1			in.	to	ft.
	ELL WATER TO BE	USED AS:				9. Dewaterii	ng 11. Inject	ion well
					nd garden only		12. Other (Spe	cify below)
		dustrial 6. Oil field w		8. Aircon YES	ditioning	10. Monitorin	ı g we ii vh <u>at</u> mo/day/yr wa	is sample
	ubmitted	ogical sample submitted to t	pepartment:		ater Well Disinfo		YES N	
5 TYPE OF CASING USED:	5. Wrought Iro	on 7. Fiberglass	9. Ot	ther (Specify	below) CAS	ING JOINTS: (Glued	Threaded
1. Steel 3. RPM (SI	R) 6. Asbestos-C	· ·	sDI	R-26			Welded	Clamped
2. PVC 4. ABS Blank casing diameter 5	in. to 80			4-	4 1	Dia. i	i to	ft.
	10	,	in.	to			in. to	П.
Casing height above land surface: TYPE OF SCREEN OR PERFORATION	,	Weight:	2.35 It	os. / ft.	waii thi	ckness or gaug	ge No214	
1. Steel 3. Stainless Steel	5. Fiberglass	7. PVC	9. A	BS	11. Oth	ner (specify)		
2. Brass 4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. A	sbestos-Cen	nent 12. No	ne used (open	hole)	
SCREEN OR PERFORATION OPENING	GS ARE:							
1. Continuous slot 3. Mill sl	lot 5. Gai	uzed wrapped	7. To	rch cut	9. Drille	ed holes	11. None (op	en hole)
2. Louvered shutter 4. Key p	unched 6. Wir	re wrapped	8. Sa	w cut	10. Othe	er (specify)		
SCREEN - PERFORATION INTERVAL	From	80 ft. to	100	ft.,	From	ft.	to	ft.
	From	ft. to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	24 ft. to	100	ft.,	From	ft.	to	ft.
	From	ft. to	,	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat	cement	2. Cement Grout	3	3. Bentonite		Other bent	onite hole plu	3
Grout Intervals: From 4		24 ft., From	ft.	to	ft.,	From	ft. to	ft.
What is the nearest source of possible control of the state of the sta	7 D	it privy 1	0. Livestoc	k pens	13. Insectio	cide storage	15. Oil well/Ga	s well
· ·						16. Other (spe	cify below)	
3. Watertight sewer line 6. Seepa		eed yard	12. Fertilize	r storage				
Direction from well? East					How ma	ny feet? 10 f		
	LITHOLOGIC I	LOG	From	То		LITHOLO	GIC LOG	
0 3 topsoil 3 30 clay				 				
30 45 fine sand								
45 80 clay								
80 100 medium sand	i							***
			 					
					•			
		****	ļ	ļļ				
				 	-			
			_			.,		
7							and an array to the state of the	
7 Contractor's or Landowner's Certifi				constructed			under my jurisdictio	n and
was completed on (mo/day/year)	6/29/18				knowledge and b			
Kansas Water Well Contractor's Licen	ise No. 236	This water we	ell record wa	s completed	on (mo/day/yea		2/18	
under the business name of Harp	Well and Pump	Service	by (si	gnature)	\mathcal{T}	odd S	. Harp	