WATER WELL RECORD Form WWC-5 RANGE NUMBER SECTION NUMBER TOWNSHIP NUMBER LOCATION OF WATER WELL: FRACTION NW11 27 R 2W E/W Sedgwick SE 1/4 1/4 Distance and direction from nearest town or city street address of well if located within city? 1426 N. Kentucky Lane Wichita, Kansas **COMFORT HOMES** WATER WELL OWNER: Board of Agriculture, Division of Water Resource 4313 N. 119th W. RR#,ST. ADDRESS,BOX #: ZIP CODE: 67101 Maize, Kansas Application Number: CITY, STATE: 70 **ELEVATION** 4 DEPTH OF COMPLETED WELL: ft. LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft ft. Depth of groundwater Encountered: Ν 10/30/18 WELL'S STATIC WATER LEVEL 35 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm NW -NE ft. after hours of pumping @ gpm Est. Yield: Well water was qpm Φ 70 ≌ 12 in. ft. Bore Hole Diameter in. and to WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample (NO) Was a chemical/bacteriological sample submitted to Department? (YES) NO Was Water Well Disinfected? submitted 5 TYPE OF CASING USED: CASING JOINTS: Clued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 5 Blank casing diameter to 50 Dia. to Dia in. to ft. 12 2.35 Casing height above land surface: in., Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 7. PVC 9 ABS 11. Other (specify) Fiberglass 1. Steel 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 9. Drilled holes 11. None (open hole) 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 8. Saw cut 2. Louvered shutter 10. Other (specify) 6. Wire wrapped 4. Key punched SCREEN - PERFORATION INTERVAL 50 70 ft. ft., From From to ft. to ft. From to ft., From ft. to ft. 24 **GRAVEL PACK INTERVALS:** to 70 From ft., From ft to ft. From ft. to ft.. From ft. GROUT MATERIALS: Other 6 bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From ft. 24 ft.. From ft ft., From ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 3. Watertight sewer line 6 12. Fertilizer storage 9. Feed yard 6. Seepage pit How many feet? 50 ft. plus Direction from well? From LITHOLOGIC LOG LITHOLOGIC LOG To From То topsoil 3 35 clay 35 50 fine sand 50 70 medium sand under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged 10/30/18 and this record is true to the best of my knowledge and belief. was completed on (mo/day/year) 11/01/18 This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236 Todd S. Harb by (signature) under the business name of Harp Well and Pump Service

KSA 82a-1212