WATER WELL RECORD FO	orm WWC-5 KSA	A 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER	TOWNSHIP NUMBER	RANGE NUMBER
Sedgwick NW 1/4 SE 1/4 SW	1/4 26	T 27 S	R 2W E/W
Distance and direction from nearest town or city street address of well if located within city?			
1307 S. Fawnwood Wichita, Kansas  2 WATER WELL OWNER: SHARP HOMES			
2 WATER WELL OWNER: SHARP HOMES  RR#.ST. ADDRESS,BOX #: Board of Agriculture, Division of Water Resource			
CITY, STATE: Wichita, Kansas	ZIP CODE: 6720	06 Application Num	ber:
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 110		EVATION:	
WITH AN "X" IN SECTION BOX:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 30		ACE MEASURED ON mo/d	av/vr: 2/7/19
Pump test data: Well water			of pumping @ gpm
NY NE		ft. after hours	of pumping @ gpm
Est. Yield: gpm Well water Set Williams Set	to 116 ft.	and in.	to ft.
WELL WATER TO BE USED AS:	7 Jawa and	9. Dewaterin	•
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below) 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well			
2. Irrigation 4. Industrial 6. Oil field wa Was a chemical/bacteriological sample submitted to De			vhat mo/day/yr was sample
submitted		er Well Disinfected?	YES NO
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass	9. Other (Specify be	low) CASING JOINTS: (	Glued Threaded
1. Steel 3. RPM (SR) Welded Clamped			
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile			
Blank casing diameter 5 in. to 40 ft., Dia.	in. to	•	in. to ft.
	2.35 lbs. / ft.	Wall thickness or gaug	ge No214
TYPE OF SCREEN OR PERFORATION MATERIAL:  1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)			
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)  2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:  1. Continuous slot  3. Mill slot  5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None ( open hole)
			· · · · · · · · · · · · · · · · · · ·
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 40 ft. to	116 ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft. to	116 ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite	Other bent	onite hole plug
Grout Intervals: From ft. to ft., From	ft. to	ft., From 4	ft. to 24 ft.
What is the nearest source of possible contamination:  1. Septic tank 4. Lateral lines 7. Pit privy	). Livestock pens	13. Insecticide storage	15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)			
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage			
Direction from well? South		How many feet? 10 f	t plus
From To LITHOLOGIC LOG	From To	LITHOLO	GIC LOG
0 3 topsoil			
3 18 clay			
18 26 fine sand 26 116 gray shale			
26 116 gray shale			
		<del></del>	
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and			
was completed on (mo/day/year) 2/7/19 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 2/11/19			
under the business name of Harp Well and Pump Service by (signature)  Todd S. Harb			