WATER WELL RECORD Form WWC-5 KSA 82a-1212
1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER
Sedgwick NE 1/4 SW 1/4 SE 1/4 13 T 27 S R 2W E/W
Distance and direction from nearest town or city street address of well if located within city? 732 N. Thorton Ct. Wichita, Kansas
2 WATER WELL OWNER: NIES CONSTRUCTION Record of Agriculture Division of Water Resource
RR#,ST. ADDRESS,BOX #: 10333 E. 21st N. #303
CITY, STATE: Wichita, Kansas ZIP CODE: Application Number:
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION:
WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft.
WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 4/3/19
Pump test data: Well water was ft. after hours of pumping @ gpm by Est. Yield: gpm Well water was ft. after hours of pumping @ gpm
Est. Yield: gpm Well water was ft. after hours of pumping @ gpm \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
WELL WATER TO BE USED AS:
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chamical fracteriological sample submitted to Department? VES. NO. ; If yes, what mo/day/yr was sample
S Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO
5 TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded
1. Steel 3. RPM (SR) Welded Clamped
2. PVC 4. ABS 6. Aspestos-cement 6. Concrete tile
Casing height above land surface: 12 in., Weight: 2.23 lbs. / ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL:
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)
SCREEN - PERFORATION INTERVAL From 80 ft. to 100 ft., From ft. to ft.
From ft. to ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 24 ft. to 100 ft., From ft. to ft.
From ft. to ft., From ft. to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug
Grout Intervals: From ft. to ft., From ft. to ft., From 4 ft. to 24 ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage
Direction from well? South How many feet? 20 ft plus
From To LITHOLOGIC LOG From To LITHOLOGIC LOG
0 3 topsoil
3 29 clay 29 65 fine sand
65 75 clay
75 100 medium sand
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and
was completed on (mo/day/year) 4/3/19 and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4/4/19
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp