	WATER W	ELL RECO	DRD F	orm WV	VC-5 K	SA 82a-121	2			
1 LOCATION OF WATER WELL:	FRACTION			1	TION NUMBER	1		RANGE NUMBER R 2W E/W		
Sedgwick Sedgwick	NW 1/4	NW 1/4		1/4	24	T 27	S	R 2W	E/W	
Distance and direction from nearest town or city s			-							
12521 W. Jennie Ct.	L CONSTRU	ita, Kansa	ıs							
	W. 21st N.	CHON					Board of Agri	culture, Division of W	ater Resource	
	ita, Kansas			7	IP CODE:		Application Nun	nber:		
	EPTH OF COMP	LETED WELL	. 10			ELEVATION:				
WITH AN "X" IN SECTION BOX:	th of groundwater			fi			ft.		ft.	
1 .	LL'S STATIC WA		25			JRFACE MEASU	RED ON mo/o	tav/vr: 3/18	/19	
		mp test data:	Well wate		JIV LAND OC	ft. after		of pumping @	gpm	
	Est. Yield:	gpm	Well wat			ft. after		of pumping @	gpm	
₩ E Bo	ore Hole Diameter	10	in.	to	100 ft.	and	in.	to	ft.	
	LL WATER TO B	E USED AS:					9. Dewateri	ng 11. Injed	tion well	
1.	Domestic 3.	Feedlot 5	. Public wat	ter supply		and garden only		12. Other (Sp	ecify below)	
	•		. Oil field wa		•		10. Monitorii	n g we u what mo/day/yr w	as sample	
ŭ	as a chemical/bacter omitted	nological sample	submitted to D	epartment?	YES Was V	NO Water Well Disinfo			10	
5 TYPE OF CASING USED:	5 Marian 194		- Cib a selecc	9.0	ther (Specify	(below) CAS	ING JOINTS: (Glued	Threaded	
1. Steel 3. RPM (SR	5. Wrought		. Fiberglass	SD	R-26	20.011,		Welded	Clamped	
2. PVC 4. ABS	6. Asbestos	s-Cement 8	. Concrete til	le SD	K-20					
Blank casing diameter 5	in. to	80 ft.,	Dia.	in.	to	ft., I	Dia.	in. to	ft.	
Casing height above land surface:	12 in.,	,	Weight:	2.35	lbs. / ft.	Wall thi	ckness or gau	ge No214		
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)										
2. Brass 4. Galvanized	Concrete T	ile 8.	RMP (SR)	10. /	Asbestos-Cei	ment 12. No	ne used (open	hole)		
SCREEN OR PERFORATION OPENING	S ARE:									
1. Continuous slot 3. Mill sid	ot 5. C	Gauzed wrapp	ed	7. To	orch cut	9. Drill e	ed holes	11. None (o	pen hole)	
2. Louvered shutter 4. Key pu	inched 6. V	Wire wrapped		(8. S .	aw cut	10. Othe	er (specify)			
SCREEN - PERFORATION INTERVAL	From	80 ft.	to	100	ft.,	From	ft.	to	ft.	
	From	ft.	to		ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	From	24 ft.	to	100	ft.,	From	ft.	to	ft.	
	From	ft,	to		ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1 Neat								onite hole plu		
GROUT MATERIALS: 1. Neat of Grout Intervals: From 4	ft. to	2. Cement 24 ft			3. Bentonite			•	9	
What is the nearest source of possible co		24 ft.,	From	ft.		ft.,	From	ft. to	ft.	
1. Septic tank 4. Lateral lines 7. Pit privy 10. Live					ck pens	pens 13. Insecticide storage 15. Oil well/Gas well				
2. Sewer lines 5. Cess P	ool 8	. Sewage lago	oon 1	1. Fuel sto	orage	14. Abande	on water well	16. Other (sp	ecify below)	
3. Watertight sewer line 6. Seepag	gepit 9	. Feed yard	1	2. Fertilize	er storage					
Direction from well? West						How ma	ny feet? 10			
	LITHOLOGIC	CLOG		From	То		LITHOLO	OGIC LOG		
0 3 topsoil				 	+					
3 15 clay 15 35 fine sand					 					
15 35 fine sand 35 75 clay					†					
75 97 medium sand										
97 100 clay										
					-					
					-					
		· · · · · · · · · · · · · · · · · · ·								
				L	1					
7 Contractor's or Landowner's Certific	cation: This water	well was 1.	constructed) 2. r	econstructe	d or 3. I	plugged	under my jurisdict	on and	
was completed on (mo/day/year)	3/18/19	and	this record i	is true to th	e best of my	knowledge and b	oelief.			
Kansas Water Well Contractor's Licens	se No. 236	٦	This water we	ell record w	as completed	d on (mo/day/yea	r) 3/2	20/19		
under the business name of Harp Well and Pump Service by (signature) Todd S. Harb										