		WATER W	VELL RE	CORD	Form V	WC-5	(SA 82a-12	12			
1 LOCATION OF WATER WELL:		FRACTION NIE 444 STE				ECTION NUMBE	1	TOWNSHIP NUMBER T 27 S		RANGE NUMBER R 2W E/W	
Sedgwick		NE 1/4		1/4 SE	1/4	11	<u> </u> T 2	27 S	R 2\	V E/W	
Distance and direction fro 1710 N. Nicke			Wichita.								
2 WATER WELL		MP, Alexis	· · · · · · · · · · · · · · · · · · ·	ILMIISUS							
RR#,ST. ADDRESS,BOX #: 1710 N. Nickelton Circle											
CITY,	STATE: Wich	ita, Kansas				ZIP CODE:		Application Nur	nber:		
3 LOCATE WELL'S LO		DEPTH OF COM	PLETED W	/ELL:	70	ft.	ELEVATION:				
WITH AN "X" IN SEC	Dep	oth of groundwate	er Encounte			ft.		ft.		ft.	
	WE	ELL'S STATIC W	ATER LEVI			LOW LAND S	URFACE MEAS			2/19	
	NE		ump test da		ater was		ft. after		s of pumping @ s of pumping @	gpm gpm	
w Mie	F B	Est. Yield: ore Hole Diamete	gpm er 12		vater was to	<b>70</b> ff	ft. after t. and	in.	to	ft.	
- "	' XI I	ELL WATER TO		AS:				0 Dewateri	44 1-1	ction well	
sw	SE 1.	Domestic 3	3. Feedlot	5. Public v	vater supp	ly 7. Lawn	and garden on		12. Other (S	pecify below)	
	_	•	f. Industria			P-7	nditioning	10. Monitoria	<b>ng well</b> what mo/day/yr	was sample	
s		/as a chemical/bact omitted	enological sal	mpie submitted t	o Departmen		NO Water Well Disir			NO	
5 TYPE OF CAS	SING USED:	5. Wrough	nt Iron	7. Fiberglas	s 9	. Other (Specif	fy below) CA	SING JOINTS:	Glued	Threaded	
1. Steel	3. RPM (SR	κ) -		•	c	DR-26	•		Welded	Clamped	
2. PVC	> 4. ABS		os-Cement	8. Concrete	e tile -						
Blank casing diamete	er 5	in. to	50 ft.,	, Dia.	in		ft.,	Dia.	in. to	ft.	
Casing height above		12 in.,		Weight:	2.35	lbs. / ft.	Wall t	hickness or gau	ge No214	<b>,</b>	
	TYPE OF SCREEN OR PERFORATION MATERIAL:  1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)										
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)											
SCREEN OR PERFO	DRATION OPENING	S ARE:									
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None ( open hole									open hole)		
2. Louvered shutte	er 4. Key pu	unched 6.	. Wire wrap	ped	<b>(8</b> .	Saw cut	10. Oth	ner (specify)			
SCREEN - PERFORA	ATION INTERVAL	From	50	ft.	to 70	ft.,	From	ft.	to	ft.	
		From		ft.	to	ft.,	From	ft.	to	ft.	
GRAVEL PA	CK INTERVALS:	From	24	ft.	to 70	ft.,	From	ft.	to	ft.	
		From		ft.	to	ft.,	From	ft.	to	ft.	
6 GROUT MATER	IALS: 1. Neat o	cement	2. Cem	nent Grout		3. Bentonit	e	Other bent	tonite hole pl	ug	
Grout Intervals: From ft. to ft., From ft. to ft.,							From 4	ft. to	24 ft.		
What is the nearest s	•		7. Pit privy	,	10. Lives	tock pens	13. insec	ticide storage	15. Oil well/	Gas well	
1. Septic tank 4. Lateral lines 4. Cateral lines 5. Cateral lines 5. Cateral lines 5. Cateral lines 6. Cater								pecify below)			
2. Sewer lines	_	001	9. Feed yar	-	12. Fertil	izer storage					
3. Watertight sewer line 6. Seepage plt 9. Feed yard 12. Fertilize Direction from well? East							How many feet? 50 ft. plus				
From To	I	LITHOLOG	IC LOG		Fror	n To		LITHOLO	OGIC LOG		
0 3	topsoil						<u> </u>				
3 22 22 47	clay fine sand				+	<del></del>					
47 70	medium sand										
					<del></del>		<del> </del>				
<del></del>	<del> </del>					+					
							,,				
								*****			
		×			+		ļ				
				,-w-							
7 Contractor's or	Landowner's Certific	cation: This water	er well was 1	1. construct	<b>ed</b> 2.	reconstructe	ed or 3.	plugged	under my jurisdic	tion and	
was completed on	(mo/day/year)	5/22/19		and this reco	rd is true to	the best of my	knowledge and	belief.			
Kansas Water Wel	l Contractor's Licens	se No. 236		This water	well record	was complete	ed on (mo/day/ye	ar) 5/2	23/19		
under the business name of Harp Well and Pump Service by (signature)  Todd S. Havb											