		WATER V	VELL R	ECORD	Form V	VWC-5	(SA 82a-	1212					
1 LOCATION OF WAT	ER WELL:	FRACTION				ECTION NUMBE				RANGE NUMBER			
Sedgwick		NW 1/-	•	1/4 SW	/ 1/4	28		27	s	R	2W	E/W	
Distance and direction for		•		within city?									
2526 E. Dory		<u>Wichita, F</u> AUSMEYER		TRUCTIO	N								
RR#,ST. ADDRES		08 W. York						Boa	ard of Agric	ulture, Divisio	n of Wat	er Resource	
CITY	, STATE: Wid	chita, Kansas	S			ZIP CODE:	·	Applic	ation Numb	per:			
3 LOCATE WELL'S		DEPTH OF COM	IPLETED V	VELL:	120	ft.	ELEVATIO	ON:					
WITH AN "X" IN SE	D	epth of groundwa	ter Encount	ered:		ft.		f	t.			ft.	
	v	VELL'S STATIC W	VATER LEV	'EL 30	FT. BE	LOW LAND S	URFACE ME	EASURED (ON mo/da	ay/yr:	7/22/1	9	
NW NW	NE		ump test da		vater was		ft. afte			of pumping	_	gpm	
w Mile		Est. Yield: Bore Hole Diamet	gpm ter 1		vater was	120 ff	ft. afte t. and			of pumping	@ to	gpm ft.	
2 "	1 1	VELL WATER TO		*****	10	120	t. and		in. Jewaterin			on well	
Sw			3. Feedlot	5. Public v	vater supp	ly 7. Lawn	and garden	only 9. L	ewaterin	8	-	cify below	
		2. Irrigation	4. Industria	al 6. Oil field	water sup	ply 8. Air co	nditioning		Monitoring	g well			
S		Was a chemical/bac	teriological sa	ample submitted t	o Departmer		NO Water Well D		_	hat mo/day	y/yr was NO		
5 TYPE OF CA	SING USED:							CASING J		Glued		hreaded	
1. Steel	3. RPM (S	5. Wroug SR)	ht Iron	7. Fibergla	30	Other (Specif	y below)	CASING N		Welded		Clamped	
2. PVC	A. ABS	6. Asbest	tos-Cement	8. Concrete	e tile	DR-26							
Blank casing diame	ter 5	in. to	36 ft	., Dia.	in	to	ft.,	Dia.	ir	n. to	כ	ft.	
Casing height abov	e land surface:	12 in.,		Weight:	2.35	lbs. / ft.	W	all thickness	s or gauge	e No.	214		
TYPE OF SCREEN							4.						
1. Steel	3. Stainless Steel	5. Fiberglas		7. PVC		. ABS		1. Other (sp	•	(مام)			
2. Brass	4. Galvanized	6. Concrete	e ille	8. RMP (SR	, 10). Asbestos-Ce	ement 14	2. None use	a (open n	iole)			
SCREEN OR PERF			. Gauzed w	rannad	7	Torch cut	0	Drilled hol	00	11 No.	ne (one	en hole)	
										11.110	пе (оре	iii iiole;	
2. Louvered shut	ter 4. Key	punched 6	i. Wire wrap	pped	_	Saw cut	10.	Other (spe	сіту)				
SCREEN - PERFOR	RATION INTERVAL	- From	36	ft.	to 12) ft.,	From		ft.	to	ס	ft.	
		From	2.4	ft,	to	ft.,	From		ft.	to)	ft.	
GRAVEL P	ACK INTERVALS:	From	24	ft.	to 12	J ft.,	From		ft.	to)	ft.	
		From		ft.	to	ft.,	From		ft.	to		ft.	
6 GROUT MATER	1. 1160	t cement		nent Grout		3. Bentonite		Other		nite hol		_	
Grout Intervals: What is the nearest:	From	ft. to	0	ft., From	4	ft. to	24 ft	., Fro	m 43	ft.	to 4:	5 ft.	
1. Septic tank	4. Later		n: 7. Pit privy 10			. Livestock pens		13. Insecticide storage 15			. Oil well/Gas well		
2 Sewer lines	5. Cess	Pool	8. Sewage	lagoon	11. Fuel	storage	14. A t	oandon wa	er well	16. Othe	er (spec	ify below)	
3. Watertight sew	rer line 6. Seep	age pit	9. Feed ya	rd	12. Fertil	zer storage							
Direction from well?	South						Ho	w many fee					
From To		LITHOLOG	IC LOG		Fror	n To	 	LIT	HOLO(GIC LO	<u> </u>		
$\begin{array}{c c} 0 & 3 \\ \hline 3 & 26 \end{array}$	topsoil clay				 								
26 42	fine to medi	um sand			+								
42 120	grey shale												
													
					- 		1						
							ļ						
	-						 						
						<u> </u>							
	1				+		 						
7 Contractor's or	Landowner's Certi	ification: This wat	er well was	1. construct	ed 2.	reconstructe	ed or 3.	plugge	e d u	nder my jur	isdiction	and	
was completed or	n (mo/day/year)	7/22/19		and this reco	d is true to	the best of my	knowledge a	and belief.					
Kansas Water We	ell Contractor's Lice	nse No. 236		This water	well record	was complete	d on (mo/dav	y/year)	7/24	1/19			
	s name of Har p		ımp Serv			(signature)	•	Tod	_	_	ν'n		
	P			-					WW 41-		- I <i>j</i>		