			WATER V	VELL RE	CORD	Form	WWC-5	KSA	82a-	1212				
11.1	ATION OF W	ATER WELL:	FRACTION				SECTION NUMB			ISHIP NUM	MBER	RANGE NUMBER		
	dgwick		NE 1/4		1/4 SE	C 1/4	20		T	27	S	1	R 2V	
		from nearest town or city s												
		arstone Ct		d, Kansas										
	ATER WEL		L CONSTR	RUCTION						_				
RR#,	ST. ADDRE		W. 21st N					(B00)	_	В	oard of Agr	iculture, Div	ision of V	/ater Resou
0			ita, Kansas				ZIP CODE:	67205	5	Appl	ication Nun	nber:		
	CATE WELL'S TH AN "X" IN S	LOCATION A D	EPTH OF COM	PLETED WE	LL:	120	ft.	ELE	VATIO	N:				
		Dept	h of groundwate	er Encountere	ed:		ft.				ft.			ft.
	1	WE	L'S STATIC W	ATER LEVEL	. 32	FT. B	ELOW LAND	SURFAC	CE MEA	ASURED	ON mo/o	lav/vr	9/24	
1' 1	WM	NE	Pu	ump test data:	Wellw	ater was			t. after			of pumpir		_
w Wile	1		Est. Yield:	gpm	Well v	vater was		1	ft. after			of pumpir		g 91
≅ w⊦	_	E Bor	e Hole Diamete	r 12	in.	t	120	ft.	and		in.	a. pampii	to	91
-	-21.		L WATER TO I	BE USED AS:						10	Dewaterir	a 1		tion well
111	SW		Domestic 3	. Feedlot	5. Public w	ater sup	oly 7 Lawr	and ga	ırden o	nly	seware: !!	-0	-	ecify belo
				. Industrial	6. Oil fleld	water su	pply 8. Air c	ondition	ing		Monitorin	g well		
	S	Was	s a chemical/bacte	eriological sampl	e submitted to	Departme		<	NO)	; If yes, w	/hat mo/d	ay/yr wa	as sample
5 1	TVDE OF C	ASING USED:	inted							sinfected?	(YES)	N	0
티 .	1. Steel	3. RPM (SR)	Wrought	Iron	7. Fiberglas	s g	. Other (Speci	ify below	/) C	ASING J	OINTS: 🤇	Glued		Threaded
_	2. PVC	4. ABS	6. Asbesto	s-Cement	8. Concrete	tile S	SDR-26					Welded		Clamped
Blank c	asing diame						4							
			10	40 ft.,	Dia.	in	. to	1	ft.,	Dia.	ir	1.	to	ft.
1	-	re land surface:	12 in.,		Weight:	2.35	lbs. / ft.		Wall	thickness	or gauge	∍ No.	.214	
		OR PERFORATION M			B) (0)									
1. St		3. Stainless Steel	5. Fiberglass		. PVC). ABS			Other (sp	• ,			
2. Br	ass	4. Galvanized	6. Concrete T	ïle 8	. RMP (SR)	10). Asbestos-Ce	ement	12. I	None use	d (open h	ole)		
SCREEN	N OR PERF	ORATION OPENINGS	ARE:											
1. Con	itinuous slo	t 3. Mill slot	5. 0	Sauzed wrap	ped	7.	Torch cut		9. Dr	illed hole	es	11. No	ne (ope	en hole)
2. Lou	vered shutt	er 4. Key pund	hed 6. V	Vire wrapped	I	(8.	Saw cut		10. Ot	her (spe	cifu)		` .	,
SCREEN	. PERFOR	ATION INTERVAL	From	40 ft.		120		_		(0)0	· y /			
		THOMATERVAL			to			Fro		f	t.	t	0	ft.
	GRAVEL PACK INTERVALS:			From ft.			ft.,	From		fl	ft.		0	ft.
(GRAVEL PA	ICK INTERVALS:	From	24 ft.	to	120	ft.,	Fro	m	fi	t.	to	D	ft.
			From	ft.	to)	ft.,	Fro	m	ft		to	3	ft.
6 GRO	OUT MATER	IALS: 1. Neat cen	nent	2. Cement	Grout		3. Bentonite	,		Other	hentor	nite hol		
	t Intervals:		ft. to	ft.,	From	4	ft. to	24	ft.,	From		ft.	to 34	4
What is th	ne nearest so	ource of possible conta	mination:	Bu .			-		11.,	71011	1 32	IL.	10 34	ft.
1. Sept	ic tank	4. Lateral lin		Pit privy	0. Livest	ock pens	13. Insecticide storage 15. Oil well/Gas well							
2. Sewer lines 5. Cess Pool 8. Sewage lagoon							torage	14. Abandon water well 16. Other (specify below)						
	rtight sewe	r line 6. Seepage p	oit 9.	Feed yard	1	2. Fertiliz	er storage							
	from well?	West							How m	nany feet?	20 ft.	plus		
From	То	LIT	HOLOGIC	LOG		From	То					IC LO	3	
_0	3	topsoil												
3	27	clay					-							
27	32	fine sand				_								
32	120	grey shale				-	-							
							+	_						
							+ +							
							+							
									_					
Contr	actor's or La	indowner's Certification	: This water we	ell was 1. Ccc	nstructed) 2 re	constructed	or	3.	plugged	und	er my juris	diction -	nd
		no/day/year)	9/24/19				e best of my k				ande	my juns	aiodoli a	iiu
								_						1
		Contractor's License No			s water well	record wa	as completed of	on (mo/o	lay/yea	r)	9/25/1	9		
under the	business n	ame of Harp Wel	l and Pump	Service		by (s	ignature)		To	odd	S. i	Har	ъ	