2-0-			WATE	R WELL	REC	ORD	Form '	WWC-5	KSA	82a-	1212				
10.4	1 LOCATION OF WATER WELL: FRACTION SW 1/4 SW 1/4 N							SECTION NUME	TO THE PARTY OF TH				RANGE NUMBER		
-			SW	1/4 SV			1/4	23		T	27	S		R 2	W E/W
		from nearest town or				•									
		<b>lighland Spri</b> r  L OWNER: <b>D</b> A	AVIS, Mike		Vicnita	a, Kansa	as								
	ST. ADDRE		628 W. Hig		ringe	Ct					В	oard of Agr	iculture D	livision of	Water Resou
1,		Y, STATE: W	ichita, Kan	sas	n mgs	Ci.		ZIP CODE:	6723	5				TVISION O	Water Nesou
3 100	ATE WELL'S		4 DEPTH OF		D WELL		78	ft.				ication Nun	nber:		
WIT WIT	H AN "X" IN S	SECTION BOX:	—				, 0		ELE	VATIO	NY:				
lı r	1		Depth of ground WELL'S STATI			27		ft.				ft.			ft.
11 1	NW		WELLSSIAII					ELOW LAND S							5/19
0	141/4	NE	Est. Yield:	Pump tes			ater was ater was			ft. after			of pump		g
w Wile	1	K	Bore Hole Dia		om 12	in.	ater was to	78	t.	ft. after and	,		of pump		gi
=		,	WELL WATER					70	ι.	and		in.		to	
1 1	sw		1. Domestic	3. Feedle	ot 5	. Public w	ater supp	ly 7. Lawn	and g	arden d	only 9. I	Dewaterir	_	-	ction well
	· ·		2. Irrigation	4. Indust				ply 8. Air co	nditio	ning	10,	/onitorin	ا ع.ر g well	omer (5)	pecify belo
-	9		Was a chemical	/bacteriologica	l sample s	submitted to	Departmen			NO		; If yes, w	hat mo/	day/yr v	vas sample
E 7	VDE OF C	ASING USED:	submitted					Was	Water	Well Di	sinfected?		YES)		NO
5 1	1. Steel	3. RPM (	SR) 5. Wro	ought Iron	7.	Fiberglass	, 9	Other (Specif	y belov	v) C	CASING J	OINTS: 🤇	Glued	>	Threaded
_	2. PVC	4. ABS	•	estos-Ceme	ent 8.	Concrete t	tile S	DR-26					Welded		Clamped
Blank c	asing diame		in. to	50	ft.,	Dia.	in.	to		4	Die				
	_	e land surface:	10							ft.,	Dia.	ir		to	ft.
_	_	OR PERFORATION		n.,	V	Veight:	2.35	lbs. / ft.		Wal	l thickness	or gauge	∍ No.	.214	
1. St		3. Stainless Steel	5. Fiberg	lass	(7.F	PVC	Q	ABS		11	Other (spe	acifu)			
2. Br		4. Galvanized	6. Concr			RMP (SR)		Asbestos-Ce	ment		None use		\		
SCREEN	I OD DEDE	ORATION OPENIN			•	(5.1)	,,,		HOIIL	12.	INOTIC USE	a (open n	ole)		
	tinuous slo			5. Gauzed	WENDO	, el	7	Forch cut		۰. ۳					
						·u					rilled hole	_	11. N	one ( or	pen hole)
	vered shutt		punched	6. Wire wr	apped		8.	Saw cut		10. O	ther (spe	cify)			
SCREEN	- PERFOR	ATION INTERVAL	From	50	ft.	to	78	ft.,	Fre	om	f	ŧ.		to	ft.
			From		ft.	to		ft.,	Fre	om	f	t.		to	ft.
(	GRAVEL PA	CK INTERVALS:	From	24	ft.	to	78	ft.,	Fro	om	fi	<b>:</b> .		to	ft.
			From		ft.	to		ft.,	Fro	om	ff			to	
GRC	UT MATER	IALS: 1. Neat	cement	2 Ce	ment G	rout		3. Bentonite			Other				ft.
Grout	Intervals:	From	ft.	to	ft.,	From	4 f		24	4		benton 66			70
What is th	e nearest s	ource of possible c	ontamination:						27	ft.,	Fron	1 00	ft.	to 6	18 ft.
1. Sept	ic tank	4. Latera	l lines	7. Pit priv			O. Livesto		13	3. Insec	ticide sto	orage	15. <b>Oil</b>	well/Ga	s well
2. Sewe	er lines	5. Cess i	Pool	8. Sewage	e lagooi	n 1	1. Fuel st	orage	14	4. Aban	don wate	r well	16. Oth	ier (spec	cify below)
	rtight sewe	er line 6. Seepa	ge pit	9. Feed ya	ard	1:	2. Fertiliz	er storage							
	from well?	North	LITUOLO	210 1 00						How n	nany feet?				
From	To 3	100	LITHOLOG	FIC LOG			From	То			LITH	OLOG	IC LO	G	
3	25	topsoil clay						-		-					
25	42	fine sand						+ +							
42	65	medium sand												_	
65	78	grey shale													
								-							
								-							
								+							
		1													
Contr	actor's or La	andowner's Certific	ation: This wat	er well was	1. Con	structed	) 2. re	constructed	or	3.	plugged	unde	er mv iuri	isdiction	and
was com	pleted on (r	no/day/year)	9/25/19		and this	s record is	-	best of my kr					, j		
		Contractor's License						s completed o				0.00			
				~		-vaioi Well			(1110/		·	9/27/1	-		
under the	: Dusiness n	ame of Harp V	ven and Pu	ımp Serv	ice		by (si	gnature)		$T\epsilon$	odd	S.	Hau	rb	