		WATER W	ELL REC	ORD F	orm WV	√C-5 K	(SA 82a-12	12			
1 LOCATION OF W	ATER WELL:	FRACTION			SECT	TION NUMBE	R TOWNSH	IP NUMBER	RANGE NU	MBER	
Sedgwick		NW 1/4	SE 1/		1/4	13	Т 2	27 s	R 2W	E/W	
i	n from nearest town or city			city?							
727 N Tho		lichita, Kansa									
2 WATER WE		mpson, Monte	9					Board of An	riculture, Division of Wa	ntor Posouros	
RR#,ST. ADDRI		N Thornton					7225	_		iter resource	
		hita, Kansas			_	P CODE: 6		Application Nu	mber:		
3 LOCATE WELL	S LOCATION 4	DEPTH OF COMP	LETED WELL	_: 10	O ft.		ELEVATION:				
		pth of groundwate	r Encountered		ft.			ft.		ft.	
		ELL'S STATIC WA	ATER LEVEL	25	FT. BELO	W LAND SU	JRFACE MEAS	URED ON mo/	day/yr: 2/10 /	20	
Pump test data: Well water was							ft. after	hour	s of pumping @	gpm	
Mile William	!	Est. Yield:	gpm	Well wat			ft. after	hour	s of pumping @	gpm	
1 1	1 ' 1 1	ore Hole Diameter		in.	to 1	.00 ft	. and	in.	to	ft.	
SW+ ;	1 2 1 1	ELL WATER TO B		C. Darletta		7 1 num	and garden on	9. Dewater	ing 11. Injec	tion well	
sw								עצו 10. Monitori	12. Other (Sp	ecify below	
I L		2. Irrigation 4. Vas a chemical/bacte		6. Oil field w			nditioning		what mo/day/yr wa	as sample	
		bmitted	nological sample	s submitted to L	epartments	YES Was \	Water Well Disir	-	(YES) N		
5 TYPE OF	CASING USED:	5 Wrought	Iron 7	7. Fiberglass	9 0	ther (Specify	/ helow) CA	SING JOINTS:	Glued	Threaded	
1. Steel	3. RPM (SI			. Fineiglass		R-26	, 20.011,		Welded	Clamped	
2. PVC	4. ABS	6. Asbestos	s-Cement 8	3. Concrete til	e SDI	K-20					
Blank casing dia	meter 5	in. to	80 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.	
Casing height at	oove land surface:	12 in.,		Weight:	2.35 II	os. / ft.	Wall t	hickness or gau	ge No214		
TYPE OF SCREE	EN OR PERFORATION	N MATERIAL:	_						.211		
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)											
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)											
SCREEN OR PE	RFORATION OPENING	GS ARE:									
1. Continuous	slot 3. Mill sl	ot 5. 0	Gauzed wrap	ped	7. To	rch cut	9. Dri	lled holes	11. None (or	en hole)	
2. Louvered sh	utter 4. Key p	unched 6 V	Wire wrapped	ı	(8 Sa	w cut	10 Oth	ner (specify)		·	
					_			ici (opcony)			
SCREEN - PERF	ORATION INTERVAL	From	80 ft.	to	100	ft.,	From	ft.	to	ft.	
		From	ft.	to		ft.,	From	ft.	to	ft.	
GRAVEL	PACK INTERVALS:	From	24 ft.	to	100	ft.,	From	ft.	to	ft.	
		From	ft.	to		ft.,	From	ft.	to	ft.	
6 GROUT MAT	ERIALS: 1. Neat	cement	2. Cement	Grout	3	B. Bentonite		Other ben	tonite hole plu	<u>σ</u>	
Grout Intervals: From 4 ft. to 24 ft., From					ft. to		ft.,	From	ft. to	e ft.	
What is the nearest source of possible contamination:											
1. Septic tank 4. Lateral lines					0. Livestock pens			•		15. Oil well/Gas well 16. Other (specify below)	
2. Sewer lines	5. Cess I	Pool 8	. Sewage lage	oon 1	1. Fuel sto	rage	14. Aban	don water well	16. Other (spe	city below)	
3. Watertight s		ge pit 9	. Feed yard	1	2. Fertilize	r storage					
Direction from well? East							How m	nany feet? 20			
From To		LITHOLOGIC	J LOG		From	То		LITHOLO	OGIC LOG		
0 3	topsoil						-				
3 21 21 43											
43 77	1										
77 10		I									
						ļ					
											
						 					
7 Contractor's	or Landowner's Certifi	cation: This water	well was 4	aanatrusti i	<u> </u>		J 0" 0	plugged	under my designate at at		
						constructe		plugged	under my jurisdiction	лı and	
was completed	on (mo/day/year)	2/10/2020	and	this record i	s true to the	best of my	knowledge and	belief.			
Kansas Water \	Well Contractor's Licen	se No. 236	٦	This water we	II record wa	s completed	d on (mo/day/ye	ar) 2/12	2/2020		

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp