WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick \mathbf{SW} NE SW 28 1/4 27 R 2W 1/4 1/4 Т S E/W Distance and direction from nearest town or city street address of well if located within city? 2433 E Summerwood Circle Goddard, Kansas KLAUSMEYER CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 1008 W York ZIP CODE: 67215 CITY, STATE: Wichita, Kansas Application Number 116 ELEVATION: 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. N WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 5/19/20 Pump test data: Well water was ·ΝW NE ft. after hours of pumping @ gpm Est. Yield: Φ apm Well water was ft. after hours of pumping @ gpm ≌ Bore Hole Diameter 12 to 116 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering swX 5. Public water supply 7. Lawn and garden only SE 3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4 Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO (YES) submitted Was Water Well Disinfected? NO 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 7. Fiberglass 5. Wrought Iron 1. Steel 3. RPM (SR) Welded Clamped SDR-26 2. PVC 6. Asbestos-Cement 8. Concrete tile 4. ABS 5 Blank casing diameter 30 to ft., Dia. ft.. Dia in to in. to ft. 12 Casing height above land surface: in., 2.35 Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 30 From 116 ft.. From ft. ft. From ft., From ft. ft. **GRAVEL PACK INTERVALS:** 24 to 116 From ft., From ft. ft. From ft. ft., to From to ft. **GROUT MATERIALS:** Other 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From ft. to ft From ft. From 4 to 24 to ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage East Direction from well? How many feet? 20 ft. plus From Τo LITHOLOGIC LOG From To LITHOLOGIC LOG topsoil 3 21 clay 26 fine sand 21 116 26 grey shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or under my jurisdiction and plugged was completed on (mo/day/year) 5/19/2020

and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year) 5/21/2020

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb