Form WWC-5 WATER WELL RECORD KSA 82a-1212 LOCATION OF WATER WELL: **FRACTION** SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NE 1/4 NWSE 1/4 11 Т 27 S 2W E/W Distance and direction from nearest town or city street address of well if located within city? 1721 N. Throug bred Circle Wichita, Kansas DE LA TORRE, Daisy WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 1721 N Throughbred Circle ZIP CODE: 67235 Wichita, Kansas Application Number: CITY, STATE: 4 DEPTH OF COMPLETED WELL: 68 **ELEVATION:** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft. Depth of groundwater Encountered: ft. ft. WELL'S STATIC WATER LEVEL 25 5/20/20 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after apm - NW NE Est. Yield: ft. after hours of pumping @ gpm apm Well water was Ξ 12 to 68 ft Bore Hole Diameter and WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 1. Lawn and garden only SW SE 3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (YES Was Water Well Disinfected? 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 48 Blank casing diameter in to ft., Dia. to ft.. Dia in. ft. 12 2.35 Casing height above land surface: Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 3. Stainless Steel 9. ABS 5. Fiberglass 1. Steel 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 9. Drilled holes 11. None (open hole) 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 2 Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 48 68 ft. to ft., From ft. to ft. From to ft., From ft. ft. to GRAVEL PACK INTERVALS: ft. to 68 From ft.. From ft. ft. From ft. to ft., From ft. to ft. **GROUT MATERIALS:** 6 Other bentonite hole plug 2. Cement Grout 1. Neat cement 3. Bentonite Grout Intervals: From ft. to ft.. to 24 ft. to From ft. ft., What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 5. Cess Pool 14. Abandon water well 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit North How many feet? 10 ft. plus Direction from well? From To LITHOLOGIC LOG LITHOLOGIC LOG To From 0 topsoil 21 3 clay 21 clay 37 37 68 medium sand 7 under my jurisdiction and plugged

Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed 5/20/2020 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. 5/22/2020

This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp