Form WWC-5 KSA 82a-1212 WATER WELL RECORD SECTION NUMBER RANGE NUMBER 1 LOCATION OF WATER WELL: FRACTION TOWNSHIP NUMBER NW 1/4 2WSedgwick NE 1/4 1/4 36 т 27 E/W Distance and direction from nearest town or city street address of well if located within city? 12909 W. Jewell Wichita, Kansas KLAUSMEYER CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource 10008 W. York RR#,ST. ADDRESS,BOX #: ZIP CODE: 67215 Wichita, Kansas CITY, STATE: Application Number: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 120 ft. ft. Depth of groundwater Encountered: ft. WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm NW ŊE Est. Yield: Well water was ft. after hours of pumping @ gpm ≌ Bore Hole Diameter 12 to 120 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SF 1. Domestic 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? ( NO submitted Was Water Well Disinfected? (YES) TYPE OF CASING USED: 5 CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 5 to 40 Dia. ft.. to ft. Dia ft. to 12 Casing height above land surface: 2.35 Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2 Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 120 ft.. From to From ft. to From ft. to ft.. From ft. **GRAVEL PACK INTERVALS:** 24 120 From ft.. From ft. ft. From to ft., From to ft. **GROUT MATERIALS** Other 1. Neat cement 2. Cement Grout bentonite hole plug 3 Bentonite Grout Intervals: From ft to ft., From 24 39 to 40 ft. to ft., From ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 2. Sewer lines 5. Cess Pool 14. Abandon water well 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit East Direction from well? How many feet? 30 ft. plus From LITHOLOGIC LOG То LITHOLOGIC LOG From To 0 tonsoil 3 25 clay 25 37 fine sand 37 120 gray shale

Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3, plugged under my jurisdiction and was completed on (mo/day/year) 4/29/2020 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year)

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp