WATER WELL RECORD Form WWC-5 KSA 82a-1212		
1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER	RANGE NUM	BER
Sedgwick SE 1/4 SE 1/4 NW 1/4 36 T 27 S	R 2W	E/W
Distance and direction from nearest town or city street address of well if located within city?		
12922 W. Jewell Circle Wichita, Kansas		
2 WATER WELL OWNER: KLAUSMEYER CONSTRUCTION		_
RR#,ST. ADDRESS,BOX #: 10008 W. York	e, Division of Wate	er Resource
CITY, STATE: Wichita, Kansas ZIP CODE: 67215 Application Number:		
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 85 ft. ELEVATION:		
WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft.		ft.
WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON mo/day/y	r: 12/6/1	9
Pump test data: Well water was ft. after hours of p	umping @	gpm
	umping @	gpm
Est. Yield: gpm Well water was ft. after hours of p	to	ft.
WELL WATER TO BE USED AS: 9. Dewatering	11. Injection	on well
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	12. Other (Spec	cify below)
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring w	ell mo/day/yr was	s samnle
S Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what submitted Was Water Well Disinfected? YE		-
5 TYPE OF CASING USED: CASING JOINTS: COL		hreaded
1 Steel 3 RPM (SR)		Clamped
2. PVC 4. ABS 6. Asbestos-Cernent 8. Concrete tile SDR-26	idea (Jamped
Blank casing diameter 5 in. to 33 ft., Dia. in. to ft., Dia. in.	to	ft.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No	o. .214	
TYPE OF SCREEN OR PERFORATION MATERIAL:	J214	
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)		
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes	11. None (ope	en hole)
		,
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)		
SCREEN - PERFORATION INTERVAL From 33 ft. to 85 ft., From ft.	to	ft.
From ft. to ft., From ft.	to	ft.
GRAVEL PACK INTERVALS: From 24 ft. to 85 ft., From ft.	to	ft.
From ft. to ft., From ft.	to	ft.
	te hole plug	
Constitute of the Constitute o		
What is the nearest source of possible contamination:		
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage	15. Oil well/Gas	s well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well	16. Other (spec	ify below)
Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage		
Direction from well? North How many feet? 10 ft p	lus	
From To LITHOLOGIC LOG From To LITHOLOGIC	CLOG	
0 3 topsoil		
3 23 clay		
23 35 fine sand		
35 85 grey shale		

Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 12/6/19 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water we

This water well record was completed on (mo/day/year)

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp