	WATER WE	LL RECORD	Form W\	NC-5 K	SA 82a-12	12			
1 LOCATION OF WATER WELL:	FRACTION			SECTION NUMBER		TOWNSHIP NUMBER		RANGE NUMBER	
Sedgwick	NW 1/4	NW 1/4 S	E 1/4	36	T 2	7 s	R 2W	E/W	
Distance and direction from nearest town of									
2030 S. Wheatland	Wichita, Kans LAUSMEYER C		N						
	LAUSMETER C 0008 W. York	ONSTRUCTIO	14			Board of Agric	culture, Division of Wa	iter Resource	
1	Vichita, Kansas		7	IP CODE:		Application Num	ber:		
3 LOCATE WELL'S LOCATION	4 DEPTH OF COMPL	ETED WELL:	85 ft.	ii OODL.	ELEVATION:				
WITH AN "X" IN SECTION BOX:	Depth of groundwater		f	•		ft.		ft.	
N N	WELL'S STATIC WAT				IDEACE MEASI	JRED ON mo/d	ay/yr: 8/6/2		
			water was	JW LAND SC	ft. after		of pumping @	gpm	
NE	Est. Yield:	•	water was		ft. after		of pumping @	gpm	
W High	Bore Hole Diameter	12 in.	to	85 ft.		in.	to	ft.	
-	WELL WATER TO BE	USED AS:				9 Dewaterin	ng 11. Injec	tion well	
swse	1. Domestic 3. F	eedlot 5. Public	water supply	7. Lawn a	nd garden on		12. Other (Sp	cify below)	
	2. Irrigation 4. I	ndustrial 6. Oil flel	d water suppl	y 8. Air con		10. Monitorin	•		
S	Was a chemical/bacterion submitted	ological sample submitted	to Department?	YES Was W	NO Vater Well Disin		vhat mo/day/yr wa	-	
5 TYPE OF CASING USED:	I submitted						=	Threaded	
5 TYPE OF CASING USED: 1. Steel 3. RPM	M (SR) 5. Wrought li	ron 7. Fibergla	200	other (Specify	below) CA	SING JOINTS: (Glued Welded	Clamped	
2. PVC 4. ABS	6. Asbestos-	Cement 8. Concre	te tile SD	R-26			Weided	Clamped	
Blank casing diameter 5	in. to 4	0 ft., Dia.	in.	to	ft.,	Dia. i	in. to	ft.	
Casing height above land surface:	12 in.,	Weight:	2.35	lbs. / ft.	Wall th	nickness or gaug	e No214		
TYPE OF SCREEN OR PERFORA		vvoigiti.	2.00	100. 7 11.	TTGII U	nomicos of gaug	.214		
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPE	NINGS ARE:								
· I		auzed wrapped	7. To	orch cut	9. Dril	led holes	11. None (or	en hole)	
2. Louvered shutter 4. Ke	ey punched 6. W	ire wrapped	(8 S	aw cut	10. Oth	er (specify)			
			-			от (оросту)			
SCREEN - PERFORATION INTERV	AL From	40 ft.	to 85	ft.,	From	ft.	to	ft.	
	From	ft.	to	ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVAL	.S: From	24 ft.	to 85	ft.,	From	ft.	to	ft.	
	From	ft.	to	ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. N	leat cement	2. Cement Grout		3. Bentonite		Other bent	onite hole plu	g	
Grout Intervals: From	ft. to	ft., Fro	m ft	to	ft.,	From 4	ft. to 2	24 ft.	
What is the nearest source of possib	7	Pit privy	10. Livesto	ck pens	13 Insect	icide storage	15. Oil well/Ga	as well	
16 Other (energy be									
2. Sewer lines 5. Cess Pool 6. Solvey lagoon 114. Abalidon water went									
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? North How many feet? 20 ft. plus						t nlue			
From To	LITHOLOGIC	LOG	From	То	110W III	LITHOLO	_		
0 3 topsoil	<u> </u>		1.10111	1 '		LITTIOLO	OIO EOO		
3 31 clay									
31 37 fine sand									
37 85 grey shale		· 							
									
									
		·		+			· · · · · · · · · · · · · · · · · · ·		
				 					
				 					
				 					
7 Contractor's or Landowner's C	antification: This				l or 2	ulitaceq .	under my jurisdiction	n and	
				econstructed			ander my jurisuiction	and	
was completed on (mo/day/year)	8/6/2020	and this rec	ord is true to th	e best of my	knowledge and				
Kansas Water Well Contractor's L	icense No. 236	This water	r well record w	as completed	on (mo/day/yea	er) 8/7/	2020		
under the business name of Harp Well and Pump Service by (signature) Todd S. Horb									