1 LOCATION OF WATER WEL	WATE	R WELL F	RECORD.	_				
Seagwick	1.1901101	4		Form W		SA 82a-1212		
Distance and direction from neare 12830 W. Jewell (st town or city street and	1/4 SW	1/4 NV	V 1/4	ECTION NUMBER	TOWNSHIP NU	MBER	8446
12830 W. Jewell C	t. Wichita	of well if located	within city?	1/4	36	T 27	s	RANGE NUMBER R 2W FAW
WATER WELL OWNER	MCCLUBE	. Kancoc						R 2W E/W
RR#,ST. ADDRESS,BOX #	12830 W. Jews	an an						·
CITY, STATE:	Wichita, Kansa	as				В	oard of Agriculture Di	vision of Water Resource
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BO		MPI ETED W	E	Z	IP CODE: 672	235 Appli	ication Number:	rision of Water Resource
N N	Depth of groundw	ater Encounts	ELL: 8	6 ft.	E	LEVATION:	outlor Number:	·
	WELL'S STATIC	WATER LEVE	reg: :1 20	ft.			ft.	
D	1 1	Pump test data		FT. BELO	W LAND SURF	ACE MEASURED (ON mo/daysters	ft.
₩ X	Est. Yield:	ODm	a: Well wat Well wat			ft. after	hours of pumpir	9/25/20
_	Bore Hole Diame	ter 12	in	to 8	6 4	ft. after	hours of pumpir	9011
9W 9E	WELL WATER TO 1. Domestic) BE USED AS 3. Feedlot		_	- 11.	and	in.	to ft.
	2. Irrigation	4 Industrial	5. Public wat	ersupply <	7. Lawn and	garden only	ewatering 1	1. Injection well
S	Was a chemical/bac	teriological same	6. Oil field wa	ter supply	8. Air condition		12. Ot onitoring well	her (Specify below)
5 TYPE OF CASING USED	submitted		accumited to De	partment?	YES		If yes, what mo/da	IV/VI was sample
	RPM (SR) 5. Wrough	nt Iron	7. Fiberglass	9.04	vvas vvate	Diametred.	YES	NO NO
2. PVC 4. A					er (Specify belo	w) Casing Joi	NTS: Glued	Threaded
Blank casing diameter	5 in. to	35 ft.,	8. Concrete tile	SDR-	-26		Welded	Clamped
Casing height above land surface	12	33 π.,	Dia.	in.	to	ft., Dia.	in .	1
TYPE OF SCREEN OR PERFOR	ATION MATERIAL		Weight: 2	.35 lbs.	/ ft.	Wall thickness o	in. to	"
3. Stainless	Steel 5. Fiberalass	<u>7</u>	PVC			* Chickless O	gauge No.	214
4. Garvanized		-	RMP (SR)	9. ABS		Other (speci	fy)	1
SCREEN OR PERFORATION OF 1. Continuous slot 3	ENINGS ARE:		(011)	IU. ASDE	estos-Cement	12. None used (open hole)	1
	Mill slot 5. (Sauzed wrapp	ed	7 -				ı
2. Louvered shutter 4. (Key punched 6. V	Vire wrapped		7. Torch	_	9. Drilled holes	11. Non	e (open hole)
SCREEN - PERFORATION INTER	VAL From	2-		8. Saw c	ut)	10. Other (specify	')	
	From		to	86 _{ft.,}	Fro	om ft.		
GRAVEL PACK INTERVA	LS: From	ft. 24 ft.	to	ft.,	Fro		to	ft.
	From		to	86 ft.,	Fro	==	to	ft.
6 GROUT MATERIALS: 1.	leat cement	ft.	to	ft.,	Fro		to .	ft.
Glout intervals: From		2. Cement G		3. Be i	ntonite		to	ft.
What is the nearest source of possib		ft.,	From	ft.	to	ft., From	entonite hole p	
7		Pit privy	10. Liv	estock pen	I S 13	Insecticide storag	· 1	to 24 ft.
0.00	i contract of the contract of	ewage lagoor	n 11. Fu	el storage		_		
Direction from well? North	epage pit 9. F	eed yard		rtilizer stora	14. 10e	Abandon water we	ell 16. Other (specify below)
From To	LITHOLOGIC	00				How many factor 14	0.64	j
0 3 topsoil	LITHOLOGIC	<u>.OG</u>	Fr	om T	0	How many feet? 1	OGIC LOG	
3 31 clay						LITTIOL	OGIC LOG	
31 38 fine sand 38 86 grey shale								
38 86 grey shale								
7 Contractor's or Landowner's Ce	rtification: Thista	سبر ۾ ءين ال						
	9/25/2020	_		2. reconst		3. plugged	under my jurisdi	ction and
and the second to second, monitored and second								
Kansas Water Well Contractor's Li	cense No. 236	Thi	s water well rec	ord was com	npleted on (mo/		28/2020	
under the business name of Ha	rp Well and Pum	Service		by (signatur	re)	Todd	S. Har	b
L								<u> </u>