		WATER	WELL R	ECORD) Fo	rm WW	/C-5 K	SA 82a-12	12		
1 LOCATION OF WATER W	ELL:	FRACTION				SECT	TION NUMBE	1	IIP NUMBER	RANGE N	-
Sedgwick		<u> </u>	/4 SW	1/4	SE ·	1/4	11	T 2	27 s	R 2V	V EW
Distance and direction from ne 1555 N. Stout Si	_	street address of v Wichita, I		within city?							
2 WATER WELL OWN		VERT, Oliv					· · · · · ·				
RR#,ST. ADDRESS,BO	x #: 1555	N. Stout St	t. ,						Board of Agr	iculture, Division of \	Vater Resource
CITY, STA	ATE: Wich	ita, Kansas	s			ZI	P CODE: 6	7235	, Application Nur	nber:	
LOCATE WELL'S LOCAT		DEPTH OF CO	MPLETED V	NELL:	100	ft.		ELEVATION:			
N N		oth of groundwa	ater Encount	_	_	ft.			ft.		ft.
	W	ELL'S STATIC					W LAND SU		SURED ON mo/o	• •	1/20
3 '	E		Pump test d		Vell water			ft. after		s of pumping @	gpn gpn
w Z	F R	Est. Yield: ore Hole Diame	gpm eter 1	. v . 2 in.	Vell water		00 ft	ft. after . and	in.	s of pumping @ to	gpii ft.
~	, ,	ELL WATER TO		AS:					9 Deweter	44 1-1-	ction well
ısw	€ 1.	. Domestic	3. Feedlot	5. Put	olic water	r supply		and garden on		12. Other (S	pecify below
		. Irrigation	4. Industri			er supply			10. Monitori	ng well wh <u>at</u> mo/day/yr v	was sample
S		Vas a chemical/ba bmitted	icteriological s	ample submi	itted to Dep	partment?	YES Was \	NO Water Well Disi	-		NO
5 TYPE OF CASING	USED:	5. Wroug	abt leas	7 Eibo	erglass	9. O	ther (Specify	/ below) CA	SING JOINTS:	Glued	Threaded
1. Steel	3. RPM (SF	()			-		R-26	,		Welded	Clamped
2. PVC	4. ABS		stos-Cement		crete tile			_			_
Blank casing diameter	-	in. to	80 fi	•	ia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above lan		12 in.,	•	Weigl	ht: 2	.35 ii	os, / ft.	Wall	thickness or gaug	ge No214	,
TYPE OF SCREEN OR I	PERFORATION ainless Steel	1 MATERIAL: 5. Fibergla	iss (7. PVC		9. A	BS	11. C	Other (specify)		
	alvanized	6. Concret		8. RMP		10. A	sbestos-Ce	ment 12. N	lone used (open	hole)	
SCREEN OR PERFORA	TION OPENING	SS ARE:									
1. Continuous slot	3, Mill si		5. Gauzed v	wrapped		7. To	rch cut	9. Dr	illed holes	11. None (open hole)
2. Louvered shutter	4. Key pı	unched	6. Wire wra	pped		(8. Sa	w cut	10. Ot	her (specify)		
SCREEN - PERFORATIO	N INTERVAL	From	80	ft.	to	100	ft.,	From	ft.	to	ft.
		From		ft.	to	100	ft.,	From	ft.	to	ft.
GRAVEL PACK	INTERVALS:	From	24	ft.	to	100	ft.,	From	ft.	to	ft.
		From		ft.	to		ft.,	From	ft.	to	ft.
GROUT MATERIALS	S: 1. Neat (cement	2 Cei	ment Grou	ıŧ		B. Bentonite	<u> </u>		onite hole pl	
—	From .		to		From	ft.	to	ft.,	From 4	-	24 ft.
What is the nearest source	•		7. Pit priv	v	10.	Livestoc	k pens	13. Insec	ticide storage	15. Qil well/	Gas well
Septic tank Sewer lines	4. Lateral 5. Cess P		8. Sewage			. Fuel sto	-		don water well		pecify below)
	_		9. Feed ya	•		Fertilize	-	1 7. 7 3000	idon water wen		
3. Watertight sewer lin	Wes		o					How r	many feet? 2.	oft.pl	u 5
From To		LITHOLOG	SIC LOG			From	То			OGIC LOG	
	psoil										
3 25 cl	ay ne sand										
45 78 cl											
	ey shale										
				···							,
				····							····
	· · · · · · · · · · · · · · · · · · ·										
			 						ja.		
							<u></u>	<u> </u>			
7 Contractor's or Land	downer's Certific	cation: This wa	ter well was	1. Const	tructed) 2. re	constructe	d or 3.	plugged	under my jurisdic	tion and
was completed on (mo		9/21/202						knowledge and		• •	
Kansas Water Well Co							•	d on (mo/day/ye		3/2020	
					WEII					_	_
under the business nar	ine or Harp	weii and P	ump Ser	vice		by (SI	gnature)		oaas	i. Hart)