		WATER	WELL R	ECORD	Form W	NC-5 K	SA 82a-1	212			
111	1 LOCATION OF WATER WELL: FRACTION Sedgwick NW 1/4 SE 1/4 SW					CTION NUMBER	1	RANGE NUMBER			
Sedgwick	n from nearest tour	NW or city street address of	···	1/4 SW	1/4	29	T	27 S	R	2W	EW
992 N. Cas		Goddard, Kan		within city?							
2 WATER WE		KLAUSMEYE		TRUCTION	I				· · · · · · · · · · · · · · · · · · ·		
RR#,ST. ADDR		10008 W. York						Board of A	griculture, Divisio	on of Weat	er Resource
CI	ITY, STATE:	Wichita, Kansa	as			ZIP CODE: 6	7225	Application N	lumber:		
3 LOCATE WELL	'S LOCATION	4 DEPTH OF CO	OMPLETED V	WELL:	70 ft.		ELEVATIO	N:			
WITH AN "X" IN	SECTION BOX:	Depth of groundw	vater Encount	tered:	1	t.		ft.			ft.
	1	, WELL'S STATIC	WATER LEV	VEL 25	FT. BEL	OW LAND SU	IRFACE ME	ASURED ON me	o/day/yr:	1/20/	20
NW-	NE		Pump test d	lata: Well w	ater was		ft. after	hou	urs of pumping	@	gpm
₩ ₩	1	Est. Yield:	gpm		ater was		ft. after	ho	urs of pumping	@ .	gpm
	T TE	Bore Hole Diam	-	2 in.	to	70 ft.	and	in.		to	ft.
sw/	9E	WELL WATER T	3. Feedlot		ater supply	7. Lawn a	nd garden	9. Dewate	9	•	on well
	i :	2. Irrigation	4. Industria					10. Monito		er (Spe	cify below
'	S		acteriological s	ample submitted to	Department?	YES	NO	_	s, what mo/day	•	
		submitted				Was V	Vater Well D	isinfected?	(YES)	NO	<u> </u>
5 TYPE OF 1. Steel	CASING USED:	PM (SR) 5. Wrou	ight Iron	7. Fiberglas	s 9. (Other (Specify	below) (CASING JOINTS		Т	hreaded
2. PVC	- 4. AI		stos-Cement	8. Concrete	tile SD	R-26			Welded	C	Clamped
Blank casing diar		5 in. to	50 m	t., Dia.	in.	to	ft.,	Dia.	in. to		ft.
1.	bove land surface	10		Weight:		lbs. / ft.					п.
1 -		ATION MATERIAL:	••	vveignt.	2.55	IDS. / IL.	vva	II thickness or ga	uge No	214	
1. Steel	3. Stainless S		ass (7. PVC	9. /	ABS	11.	Other (specify)			
2. Brass	4. Galvanized	6. Concre	te Tile	8. RMP (SR)	10. /	Asbestos-Cer	nent 12	. None used (ope	n hole)		
SCREEN OR PE	RFORATION OP	ENINGS ARE:									
1. Continuous	slot 3.	Mill slot	5. Gauzed v	vrapped	7. T e	orch cut	9. [Orilled holes	11. No	ne (ope	en hole)
2. Louvered sh	utter 4. I	Key punched	6. Wire wra	pped	(8. S	aw cut	10. (Other (specify)			
SCREEN - PERF	ORATION INTER	VAL From	50	ft. t	o 70	ft.,					
JOOKEEN STERM	OIOTHOR INTER	From	30		0 /0	•	From	ft.	to		ft.
GPA\/EI	. PACK INTERVA		24		to 70	ft.,	From	ft.	tc		ft.
J GIVIZE	TAOR INTERVA					ft.,	From	ft.	to		ft.
6 GROUT MAT	EDIAL C	From			to	ft.,	From	ft.	to		ft.
GROUT MAT		Neat cement 4 ft.	2. Cer to 24	ment Grout	_	3. Bentonite			itonite holo		,
		ible contamination:	10 24	ft., From	ft		ft.,	From	ft.	to	ft.
1. Septic tank 4. Lateral lines 7. Pit privy 10						ck pens	13. ins	nsecticide storage 15. Oil well/Gas well			
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify									ify below)		
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage											
Direction from we							How	many feet? 20			
From To	_	LITHOLOG	GIC LOG		From	То		<u>LITHOL</u>	OGIC LO	3	
3 29	topsoil clav					 					
29 49					 						
49 65							_				
65 70	shale					 					
	 					-					
 		24			+	+		···.			
				<u>-</u>							
	ii									1	
											
 		. • .				 					
 	- 					 					
						 					
7 Contractor's	or Landowner's	Certification: This wa	ter well was	1 Constructe	d) 2, re	constructed	or 3.	plugged	under my juri	ediction	and
	on (mo/day/year	44.00.00					•		ander my jun		and
11/24/20											
under the busin	ess name of H	arp Well and P	ump Serv	rice	by (s	ignature)	7	Todds	S. Hai	rp	