	WATER WE	ELL RECORD	Form WV	VC-5 K	SA 82a-121	2		
1 LOCATION OF WATER WELL:	• • • • • • • • • • • • • • • • • • •			CTION NUMBER TOWNSHIP NUMBER			RANGE NUMBER	
Sedgwick	NW 1/4		W 1/4	28	T 2	7 s	R 2W	EW
Distance and direction from nearest town 2018 E. St. Andrews Ci	•	ard, Kansas						
	CAINELLI, Corey							····
	2018 E. St. Andrey	•				Board of Agric	culture, Division of War	er Resource
	Goddard, Kansas		z	IP CODE: 6	7052	Application Num	ber:	
3 LOCATE WELL'S LOCATION	4 DEPTH OF COMP	LETED WELL:	100 ft.		ELEVATION:			
WITH AN "X" IN SECTION BOX:	Depth of groundwater	Encountered:	п	t.		ft.		ft.
	WELL'S STATIC WAT		FT. BELO	OW LAND SU	IRFACE MEASI	JRED ON mo/da	ay/yr: 11/30/	
	Pun	np test data: We	ll water was		ft. after		of pumping @	gpn
I IX I I	Est. Yield:	gpm We	ell water was		ft. after		of pumping @	gpm
w Z	Bore Hole Diameter	12 in.	to	100 ft	and	in.	to	ft.
swse	WELL WATER TO BE			7 1 2117	and nonden and	9. Dewaterin	ng 11. injecti	on well
					and garden only	ン 10. Monitorin	12. Other (Spe	cify below
	•	Industrial 6. Oil fid iological sample submitte	eld water supply ed to Decartment?	y o. Air cor YES	NO		yhat mo/day/yr wa	s sample
:	submitted				Water Well Disin		YES NO	•
5 TYPE OF CASING USED:	5. Wrought	Iron 7. Fiberg	ulass 9. C	ther (Specify	below) CAS	SING JOINTS: (Glued 1	hreaded
	M (SR)		, en	R-26			Welded (Clamped
2. PVC 4. AE	_	•=	ete the		_			
Blank casing diameter		45 ft., Dia		to	ft.,	Dia. i	n. to	ft.
Casing height above land surface		Weight	: 2.35	bs. / ft.	Wall th	ickness or gaug	e No214	
TYPE OF SCREEN OR PERFOR 1. Steel 3. Stainless S		7. PVC		.BS	11 0	ther (specify)		
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)								
				DD00100 001		one does (open t		
SCREEN OR PERFORATION OP 1. Continuous slot 3. I		Sauzed wrapped	7 T c	orch cut	9 Ddl	led holes	11. None (op	en hole)
		• •		w cut			······································	J. 1101c)
2. Louvered shutter 4. I	Key punched 6. W	Vire wrapped		IW CUC	10. Oth	er (specify)		
SCREEN - PERFORATION INTER	RVAL From	45 ft.	to 100	ft.,	From	ft.	to	ft.
	From	ft.	to	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVA	ALS: From	24 ft.	to 100	ft.,	From	ft.	to	ft.
	From	ft.	to	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1.	Neat cement	2. Cement Grout		3. Bentonite		Other bento	onite hole plug	;
Grout Intervals: From	4 ft. to	24 ft., Fr	om ft.	to	ft.,	From	ft. to	ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy				k pens	13. Insecticide storage 15. Oil well/Gas well			
9 Several Investment 11 Steel storage						16. Other (spec	ify below)	
2. Sever miles								
3. Watertight sewer line 6. Seepage pit 9. Feed yard 1 Direction from well? West					How many feet? 50 ft. plus			
From To	LITHOLOGIC	LOG	From	То		LITHOLO	_	
0 3 topsoil								
3 28 clay								
28 55 fine sand 55 100 grev shal								
55 100 grey shal	,E	•						
				1				
				 				
	· 1							
	117							
	19.7			L				
7 Contractor's or Landowner's			icted 2. re	constructed	l or 3.	plugged u	ınder my jurisdictior	n and
was completed on (mo/day/year	11/30/2020	and this re	cord is true to the	e best of my	knowledge and I	belief.		
Kansas Water Well Contractor's	License No. 236	This wat	er well record wa	as completed	on (mo/day/yea	r) 12/3/	2020	
under the business name of Harp Well and Pump Service by (signature) Todd S. Harb								

".) S,