		n WWC-5		sion of Water			
	rd Correction Ch	ange in Well Use		urces App. No.		Well ID	
	OF WATER WELL:	Fraction		ion Number	Township Numb		
County: Sedgwick NW ¼SE ¼SW ¼SE ¼ 22 T 27 S R 2 □ E ■ W							
2 WELL OWN		First:	Street or Rura	l Address whe	re well is located	(if unknown, distance and	
Business: SHARP, CRAIG HOMES INC. Address: 2131 N. Collective Ln Ste. A							
Address:							
City: Wichita State: Kansas ZIP: 67206 231 S. Ciderbluff Ct. Wichita, Kansas 67052							
3 LOCATE WELL							
WITH "X" IN 4 DEPTH OF COMPLETED WELL: 100 ft. 5 Latitude: 37.67960							
SECTION BOX		ter Encountered: 1)		ft. Longitude: -97.52247 (decimal degrees)			
N	2) ft.	3) ft., or 4)	☐ Dry Well	Horizonta	ıl Datum: 🗷 WGS 84	$1 \square \text{ NAD } 83 \square \text{ NAD } 27$	
		ATÉR LEVEL: 25			· Latitude/Longitude:		
		below land surface, measured on (mo-day-yr).07/1				hone )	
NWNE	above land surfa	above land surface, measured on (mo-day-yr)  Pump test data: Well water was			(WAAS enabled?	Yes No)	
				☐ Land	☐ Land Survey ☐ Topographic Map		
W	E afterho	after hours pumping gpm		☐ Online Mapper:			
SW SE		Well water was					
×	Estimated Viold	after hours pumping				Ground Lovel TOC	
S	Bore Hole Diameter	Bore Hole Diameter: 12 in. to 100 ft. and			Source: Land Survey GPS Topographic Map		
1 mile		in. to			Other		
7 WELL WATER TO BE USED AS:							
5. — I done water Supply. W							
Lawn & Garde	n 7 Aquife	6. ☐ Dewatering: how many wells? 11. Test Hole: well ID 7. ☐ Aquifer Recharge: well ID ☐ Cased ☐ Uncased ☐ Geotech				Pantaghniagi	
Cased Concased Concased							
1.7 T Indication 0 = 1							
a) closed Boop   Horizontal   Veltica							
O) Open boop [] Surface Discharge [] hij. of water							
15. Office (specify).							
Was a chemical/bacteriological sample submitted to KDHE?  Yes No If yes, date sample was submitted:							
Water well disinfected? ■ Yes □ No							
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter							
Casing height above land surface							
Carlot Ca							
Office (Specify)							
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:							
Total Cut Difficultions Of Other (Specify)							
Louvered Shutter							
SCREEN-PERFORATED INTERVALS: From 30							
GRAVEL PACK INTERVALS: From 24 ft. to 199 ft., From ft. to ft., From ft. to ft.							
Grout Intervals: From A							
Grout Intervals: From4							
Sentia Tonk							
Canal Line Elvestock Felis   Insecticide Storage							
Westerfale 6 Li Sewage Lagoon - Tuel Stolage - Abandoned Water Well							
Other (Specify)							
Direction from well? South Distance from well? 22 .ft_plus ft.							
10 FROM TO	LITHOL	OGIC LOG	FROM	то Тт	IL.	PLUGGING INTERVALS	
0 3	topsoil		FROM	TO LIT	TIO. EOG (COIIC.) OF	LUGGING INTERVALS	
3 26	clay						
26 33	medium sand						
33 45	brown shale						
45 100	gray shale						
	37						
			N-4				
			Notes:				
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged							
under my jurisdiction and was completed on (mo-day-year) 0.7./11/2022 and this record is true to the best of my knowledge and belief.							
Name water Well Contractor's License No. 250 This Water Well Decord was completed on (mg. decord) 7/13/2022							
man i wind cop	y along with a ree of \$5.00 for eac	on constructed well to: Kan	sas Denartment of I	Health and Enviro	nment Bureau of Wate	r GWTS Section	
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.							
Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015							