

1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number	Range Number
County: Sedgwick	<u>NE</u>	NE ¼ SE ¼ NE ¼	13		T 27 S	R 2W E <u>W</u>
Distance and direction from nearest town or city street address of well if located within city?						<u>2 W</u>
<u>1131 Coach House Court (13th & 119th W.) Wichita, Ks.</u>						
2 WATER WELL OWNER: Mr. Paolucci				Board of Agriculture, Division of Water Resources		
RR#, St. Address, Box # : <u>1131 Coach House Court</u>				Application Number:		
City, State, ZIP Code : <u>Wichita, Ks.</u>						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>50</u> ft. ELEVATION:				
		Depth(s) Groundwater Encountered 1. .ft. 2. .ft. 3. .ft.				
		WELL'S STATIC WATER LEVEL <u>15</u> ft. below land surface measured on mo/day/yr <u>10-9-89</u>				
		Pump test data: Well water was .ft. after . hours pumping gpm				
		Est. Yield gpm: Well water was .ft. after . hours pumping gpm				
		Bore Hole Diameter <u>11</u> in. to <u>50</u> ft., and .in. to .ft.				
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <u>X</u> Clamped . Welded . Threaded .				
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile				
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)				
		7 Fiberglass Cer-mac styrene SDR-26				
Blank casing diameter <u>5</u> in. to <u>30</u> ft., Dia .in. to .ft., Dia .in. to .ft.						
Casing height above land surface <u>12</u> in., weight <u>1.59</u> lbs./ft. Wall thickness or gauge No. <u>203</u>						
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement				
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify) .				
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)				
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes						
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) .						
SCREEN-PERFORATED INTERVALS: From <u>30</u> ft. to <u>50</u> ft., From .ft. to .ft.						
GRAVEL PACK INTERVALS: From <u>24</u> ft. to <u>50</u> ft., From .ft. to .ft.						
From .ft. to .ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other .						
Grout Intervals: From <u>4</u> ft. to <u>24</u> ft., From .ft. to .ft.						
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well				
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage						
Direction from well? <u>West</u>		How many feet? <u>15</u>				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	3	topsoil				
3	19	clay				
19	31	fine sand				
31	50	medium sand				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>10-9-89</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>236</u> . This Water Well Record was completed on (mo/day/yr) <u>6-25-90</u> under the business name of <u>Harp Well and Pump Service, Inc.</u> by (signature) <u>Mary Arnold</u>						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						