

1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction NW 1/4 NE 1/4 SE 1/4	Section Number 1	Township Number T 27 S	Range Number R 2 W EW
Distance and direction from nearest town or city street address of well if located within city? 2564 Weatridge Wichita, Kansas					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Steve Harshberger 2561 Cedar Crest Wichita, Kansas Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 120 ft. ELEVATION: 25 ft.			
		Depth(s) Groundwater Encountered 1 25 ft. 2. 25 ft. 3. 25 ft. WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr 6-19-85 Pump test data: Well water was 11 ft. after 11 hours pumping 11 gpm Est. Yield 11 gpm: Well water was 11 ft. after 11 hours pumping 11 gpm Bore Hole Diameter 11 in. to 11 ft., and 11 in. to 11 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes XX No XX ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XX No XX			
		5 TYPE OF BLANK CASING USED:			
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XX Clamped XX 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded XX 7 Fiberglass Cer-Mac styrene SDR-26 Threaded XX Blank casing diameter 5 in. to 80 ft., Dia 5 in. to 80 ft., Dia 5 in. to 80 ft. Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 203			
		TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) XX 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) XX			
SCREEN-PERFORATED INTERVALS:		From 80 ft. to 120 ft., From 80 ft. to 120 ft., From 80 ft. to 120 ft. From 80 ft. to 120 ft., From 80 ft. to 120 ft., From 80 ft. to 120 ft. GRAVEL PACK INTERVALS: From 14 ft. to 120 ft., From 14 ft. to 120 ft., From 14 ft. to 120 ft. From 14 ft. to 120 ft., From 14 ft. to 120 ft., From 14 ft. to 120 ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other XX Grout Intervals: From 4 ft. to 14 ft., From 4 ft. to 14 ft., From 4 ft. to 14 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage 67 Direction from well? North How many feet? 67			
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0	3	Topsoil			
3	17	Clay			
17	31	Fine Sand			
31	55	Medium Sand and Clay			
55	80	Medium Sand			
80	83	Clay			
83	120	Medium Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-19-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 10-15-85 under the business name of Harp Well & Pump Service, Inc. by (signature) Mary Arnold					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4