

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: <u>SEDGWICK</u>		SW 1/4 SW 1/4 NE 1/4		<u>12</u>		T <u>27</u> S		R <u>2</u> EW	
Distance and direction from nearest town or city street address of well if located within city? <u>12206 Ridge Point, Wichita</u>									
2 WATER WELL OWNER:		Randy Hayes							
RR#, St. Address, Box # :		<u>12206 Ridge Point</u>				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		<u>Wichita, KS 67209</u>				Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>58</u> ft. ELEVATION:							
1 mile		Depth(s) Groundwater Encountered 1. <u>20</u> ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL <u>20</u> ft. below land surface measured on mo/day/yr <u>4-29-92</u>							
		Pump test data: Well water was <u>N/A</u> ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter <u>10</u> in. to <u>58</u> ft., and in. to ft.							
TYPE OF BLANK CASING USED:		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued <u>X</u> Clamped			
1 Steel		3 RMP (SR)		6 Asbestos-Cement		9 Other (specify below) Welded			
2 PVC		4 ABS		7 Fiberglass		Threaded			
Blank casing diameter <u>5</u> in. to <u>38</u> ft., Dia. in. to ft., Dia. in. to ft.									
Casing height above land surface <u>24</u> in., weight <u>Sch 40</u> lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC		10 Asbestos-cement					
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)			
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut		11 None (open hole)			
1 Continuous slot		3 Mill slot		6 Wire wrapped		9 Drilled holes			
2 Louvered shutter		4 Key punched		7 Torch cut		10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From <u>38</u> ft. to <u>58</u> ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>58</u> ft., From ft. to ft.									
6 GROUT MATERIAL:		1 Neat cement		2 Cement grout		3 Bentonite		4 Other	
Grout Intervals: From <u>0</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens		14 Abandoned water well					
1 Septic tank		4 Lateral lines		7 Pit privy		11 Fuel storage			
2 Sewer lines		5 Cess pool		8 Sewage lagoon		12 Fertilizer storage			
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		13 Insecticide storage			
Direction from well?		How many feet?							
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS			
0	3	top Soil							
3	25	Tight Brown Clay							
25	35	Fine Sand							
35	58	Med Gravel							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>4-29-92</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>537</u> . This Water Well Record was completed on (mo/day/yr) <u>5-27-92</u> under the business name of <u>Flowers Drilling & Pump Service</u> by (signature) <u>Miki Flowers</u>									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									