


1 LOCATION OF WATER WELL: Section Number Township Number Range Number
 County: Sedgewick SW 1/4 SW 1/4 NE 1/4 12 T 27 S R 2 EW
 Distance and direction from nearest town or city street address of well if located within city? SAME

2 WATER WELL OWNER: Diana Perachio
 RR#, St. Address, Box #: 2001 Teal Brook Court
 City, State, ZIP Code: Wichita KS 67212 60
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 15 ft.
 AN "X" IN SECTION BOX:



Depth(s) Groundwater Encountered 1. 15 ft. 2. 15 ft. 3. 15 ft.
 WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 15 ft. after 10 hours pumping 20 gpm

Est. Yield 11 gpm: Well water was 15 ft. after 10 hours pumping 20 gpm

Bore Hole Diameter 11 in. to 60 ft., and 60 in. to 60 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded

2 PVC 4 ABS 45 Fiberglass Threaded

Blank casing diameter 5 in. to 45 ft., Dia 45 in. to 60 ft., Dia 60 in. to 60 ft.

Casing height above land surface 12 in., weight 2.60 lbs./ft. Wall thickness or gauge No. 160 PVC

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 45 ft. to 60 ft., From 45 ft. to 60 ft.

From 45 ft. to 60 ft., From 45 ft. to 60 ft.

GRAVEL PACK INTERVALS: From 15 ft. to 60 ft., From 15 ft. to 60 ft.

From 15 ft. to 60 ft., From 15 ft. to 60 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 15 ft., From 3 ft. to 15 ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 28

Direction from well? EAST How many feet? 28

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 5 top soil

5 19 clay

20 28 fine sand

28 35 clay

35 60 med. sand

35 60 med. sand

35 60 med. sand

35 60 med. sand

35 60 med. sand

35 60 med. sand

35 60 med. sand

35 60 med. sand

35 60 med. sand

35 60 med. sand

35 60 med. sand

35 60 med. sand

35 60 med. sand

35 60 med. sand

35 60 med. sand

35 60 med. sand

35 60 med. sand

35 60 med. sand

35 60 med. sand

35 60 med. sand

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-21-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 9-27-91 under the business name of Weninger Drilling Inc by (signature) [Signature]