


1 LOCATION OF WATER WELL: County: <u>Sedg</u>		Fraction: <u>SW 1/4 NE 1/4 SE 1/4</u>	Section Number: <u>12</u>	Township Number: <u>T 27 S</u>	Range Number: <u>R 2 E</u>																																				
Distance and direction from nearest town or city street address of well if located within city? <u>(See below)</u>																																									
2 WATER WELL OWNER: <u>SCOTT Riffell</u> RR#, St. Address, Box #: <u>12219 Hunterview</u> City, State, ZIP Code: <u>Wichita KS 67235</u>			Board of Agriculture, Division of Water Resources Application Number:																																						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: <u>50</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>27</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>27</u> ft. below land surface measured on mo/day/yr <u>7-10-85</u> Pump test data: Well water was <u>27</u> ft. after <u>1/2</u> hours pumping <u>20</u> gpm Est. Yield <u>50</u> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: <u>1 1/2</u> in. to <u>50</u> ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Observation well 11 Injection well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No																																							
5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued <u>X</u> Clamped Welded Threaded Blank casing diameter <u>5</u> in. to <u>40</u> ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface <u>12</u> in., weight <u>1.59</u> lbs./ft. Wall thickness or gauge No. <u>SDR-16</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole) SCREEN-PERFORATED INTERVALS: From <u>40</u> ft. to <u>50</u> ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From <u>13</u> ft. to <u>50</u> ft. From ft. to ft. From ft. to ft. From ft. to ft.																																									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>3</u> ft. to <u>13</u> ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Direction from well? <u>West</u> How many feet? <u>20</u>																																									
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>2</td> <td>top soil</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>24</td> <td>clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>24</td> <td>31</td> <td>fine sand</td> <td></td> <td></td> <td></td> </tr> <tr> <td>31</td> <td>32</td> <td>clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>32</td> <td>50</td> <td>gravel</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG	0	2	top soil				2	24	clay				24	31	fine sand				31	32	clay				32	50	gravel			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG																																				
0	2	top soil																																							
2	24	clay																																							
24	31	fine sand																																							
31	32	clay																																							
32	50	gravel																																							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-10-85</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>7-10-85</u> under the business name of <u>Weninger Pully</u> by (signature) <u>[Signature]</u> INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.																																									

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4