

1 LOCATION OF WATER WELL: Fraction NW 1/4 SW 1/4 NE 1/4 Section Number 12 Township Number T 27 S Range Number R 20
 County: Edg
 Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Steve Clasen Const.
 RR#, St. Address, Box #: 756 So. Gage
 City, State, ZIP Code: Wichita KS 67218
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

NW	NE
SW	SE

4 DEPTH OF COMPLETED WELL: 75 ft. ELEVATION: 10-16-85
 Depth(s) Groundwater Encountered 1. 26 ft. 2. 26 ft. 3. 26 ft.
 WELL'S STATIC WATER LEVEL 26 ft. below land surface measured on mo/day/yr 10-16-85
 Pump test data: Well water was 26 ft. after 20 hours pumping 20 gpm
 Est. Yield 50 gpm: Well water was 26 ft. after 20 hours pumping 20 gpm
 Bore Hole Diameter 11 in. to 75 ft. and 75 in. to 75 ft.
 WELL WATER TO BE USED AS:
☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
☒ Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 7 Fiberglass Threaded X
 Blank casing diameter 5 in. to 65 ft. Dia. 65 in. to 65 ft. Dia. 65 in. to 65 ft.
 Casing height above land surface 5 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 50E-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 65 ft. to 75 ft. From 65 ft. to 75 ft.
 From 65 ft. to 75 ft. From 65 ft. to 75 ft.
 GRAVEL PACK INTERVALS: From 13 ft. to 75 ft. From 13 ft. to 75 ft.
 From 13 ft. to 75 ft. From 13 ft. to 75 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 13 ft. From 3 ft. to 13 ft. From 3 ft. to 13 ft. From 3 ft. to 13 ft.
 What is the nearest source of possible contamination:
☒ Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? North How many feet? 80

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top Soil			
2	24	Clay			
24	48	fine sand			
48	52	Clay			
52	75	med Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-16-85 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 10-16-85
 under the business name of Wagner Pully by (signature) Wagner

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4