

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		NE NE 1/4 NE 1/4	13	T 27 S	R 2 W E/W
Distance and direction from nearest town or city street address of well if located within city?					
12024 Briarwood Circle Wichita, Kansas					
2 WATER WELL OWNER: Craig Pate					
RR#, St. Address, Box # : 246 North Gleneagle Ct.			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Wichita, Kansas 67209			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION:			
1 Mile		Depth(s) Groundwater Encountered 1. 25 ft. 2. 25 ft. 3. 25 ft.			
		WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was 8-9-85 ft. after 8-9-85 hours pumping 8-9-85 gpm			
		Est. Yield 8-9-85 gpm: Well water was 8-9-85 ft. after 8-9-85 hours pumping 8-9-85 gpm			
		Bore Hole Diameter 11 in. to 11 ft., and 11 in. to 11 ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 <u>Lawn and garden only</u> 10 Observation well					
Was a chemical/bacteriological sample submitted to Department? Yes XX No XX If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes XX No XX					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 <u>RMP (SR)</u>		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued X Clamped	
2 PVC 4 <u>ABS</u>		6 Asbestos-Cement 9 Other (specify below)		Welded	
		7 Fiberglass		Threaded	
Blank casing diameter 5 in. to 30 ft. Dia.		Cer-Mac styrene SDR-26		Dia. 5 in. to 30 ft.	
Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 203					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 <u>RMP (SR)</u> 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 <u>ABS</u> 11 Other (specify)					
		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 <u>United Notes</u>					
		7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 30 ft. to 50 ft., From 30 ft. to 50 ft., From 30 ft. to 50 ft., From 30 ft. to 50 ft.					
GRAVEL PACK INTERVALS: From 14 ft. to 50 ft., From 14 ft. to 50 ft., From 14 ft. to 50 ft., From 14 ft. to 50 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 4 ft. to 14 ft., From 4 ft. to 14 ft., From 4 ft. to 14 ft., From 4 ft. to 14 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
		13 Insecticide storage			
Direction from well? 85					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Topsoil			
3	18	Clay			
18	35	Fine Sand			
35	50	Medium Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) <u>reconstructed</u> , or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-9-85 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 11-2-85					
under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Mary Arnold</i>					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					