

LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgewick		NW 1/4 SE 1/4 SW 1/4	14	T 27 S	R 2 E
Distance and direction from nearest town or city street address of well if located within city? 14410 W. Central Wichita Ks.					
WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Board of Agriculture, Division of Water Resources Application Number:			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL: 50 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 24 ft. 2. . ft. 3. . ft.			
		WELL'S STATIC WATER LEVEL 24 ft. below land surface measured on mo/day/yr 5-26-83			
		Pump test data: Well water was 30 ft. after 2 hours pumping 20 gpm			
		Est. Yield 30 gpm: Well water was . ft. after . hours pumping . gpm			
		Bore Hole Diameter: 11 in. to 50 ft., and . in. to . ft.			
		WELL WATER TO BE USED AS:			
		☒ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Injection well ☐ Irrigation ☐ Industrial ☐ Lawn and garden only ☐ Observation well ☐ Other (Specify below)			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel ☒ RMP (SR)		Welded			
2 PVC ☐ ABS		Threaded			
Blank casing diameter . in. to 30 ft., Dia . in. to . ft., Dia . in. to . ft.					
Casing height above land surface . in. weight 1.59 lbs./ft. Wall thickness or gauge No. 50k-26					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass ☒ RMP (SR)		11 Other (specify) .			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot ☒ Mill slot 6 Wire wrapped		9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut		10 Other (specify) .			
SCREEN-PERFORATED INTERVALS:		From 30 ft. to 50 ft., From . ft. to . ft.			
GRAVEL PACK INTERVALS:		From 13 ft. to 50 ft., From . ft. to . ft.			
GROUT MATERIAL:		3 Bentonite 4 Other .			
Grout Intervals: From 3 ft. to 13 ft., From . ft. to . ft., From . ft. to . ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
☒ Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? S.E.		How many feet? 130			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Topsoil			
2	22	Red clay			
22	28	fine sand			
28	38	med sand			
38	50	Charcoal shale			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-26-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 6-1-83 under the business name of Weninger Dulling by signature [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					