

1 LOCATION OF WATER WELL: Fraction SW 1/4 SE 1/4 NE 1/4 Section Number 18 Township Number T 27 S Range Number R 2 E
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city? 2 1/2 No Goddard KS (1011 No 199th West)

2 WATER WELL OWNER: Ray Holt
 RR#, St. Address, Box #: 212 Goddard KS 67052
 City, State, ZIP Code: Board of Agriculture, Division of Water Resources
 Application Number: 6-1-89

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

NW	NE
SW	SE

4 DEPTH OF COMPLETED WELL: 58 ft. ELEVATION: 38 ft. below land surface measured on mo/day/yr 6-1-89
 Depth(s) Groundwater Encountered 1. 58 ft. 2. 60 ft. 3. 20 ft.
 WELL'S STATIC WATER LEVEL 38 ft. below land surface measured on mo/day/yr 6-1-89
 Pump test data: Well water was 60 ft. after 1/2 hours pumping 20 gpm
 Est. Yield 25-30 gpm: Well water was 60 ft. after 1/2 hours pumping 20 gpm
 Bore Hole Diameter 11 in. to 95 ft., and 95 in. to 95 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 11 Injection well
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel ☒ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile ☐ CASING JOINTS: Glued X Clamped X
 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded
 7 Fiberglass ☐ Threaded SDR-26
 Blank casing diameter 5 in. to 48 ft., Dia. 48 in. to 95 ft., Dia. 95 in. to 95 ft.
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SDR-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 7 PVC ☐ 10 Asbestos-cement ☐
 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 8 RMP (SR) ☒ 11 Other (specify) SDR-26
 9 ABS ☐ 12 None used (open hole) ☐
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot ☐ 3 Mill slot ☒ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole) ☐
 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐
 7 Torch cut ☐ 10 Other (specify) SDR-26
 SCREEN-PERFORATED INTERVALS: From 48 ft. to 95 ft., From 48 ft. to 95 ft., From 48 ft. to 95 ft.
 GRAVEL PACK INTERVALS: From 30 ft. to 95 ft., From 30 ft. to 95 ft., From 30 ft. to 95 ft.

6 GROUT MATERIAL: 1 Neat cement ☐ 2 Cement grout ☒ 3 Bentonite ☐ 4 Other ☐
 Grout Intervals: From 3 ft. to 30 ft., From 3 ft. to 30 ft., From 3 ft. to 30 ft.
 What is the nearest source of possible contamination:
 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well ☐
 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☒ 11 Fuel storage ☐ 15 Oil well/Gas well ☐
 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below) SDR-26
 Direction from well? NW How many feet? 130

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soil			
2	55	Red clay			
55	95	Shale (Charcoal)			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-1-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 6-12-89 under the business name of Weninger, Diller by (signature) [Signature]