

1 LOCATION OF WATER WELL:		Fracture	Section Number	Township Number	Range Number
County: Sedgwick		NE 1/4 SW 1/4 SE 1/4	27	T 27 S	R 2 E
Distance and direction from nearest town or city street address of well if located within city?					
1 1/2 miles East + 1 Mile North of Goodard					
2 WATER WELL OWNER: Lauren Appelman					
RR#, St. Address, Box #: 17000 W. Maple					
City, State, ZIP Code: Goodard KS 67052					
Board of Agriculture, Division of Water Resources					
Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 136 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 25 ft. 2. 23 ft. 3. 11-22-91 ft.			
		WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was 23 ft. after 1 1/2 hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter . in. to . ft., and . in. to . ft.					
WELL WATER TO BE USED AS:					
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)					
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☐ If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes ☒ No ☐					
5 TYPE OF BLANK CASING USED:					
☒ 1 Steel ☐ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile CASING JOINTS: Glued ☒ Clamped ☐					
☒ 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded ☐ Threaded ☐					
Blank casing diameter . in. to . ft., Dia . in. to . ft., Dia . in. to . ft.					
Casing height above land surface . in., weight 2.60 lbs./ft. Wall thickness or gauge No. 160 PVC					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 7 PVC ☐ 10 Asbestos-cement					
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 8 RMP (SR) ☐ 11 Other (specify)					
☐ 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)					
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes					
☐ 7 Torch cut ☐ 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 36 ft. to 106 ft., From . ft. to . ft., From . ft. to . ft.					
GRAVEL PACK INTERVALS: From 23 ft. to 136 ft., From . ft. to . ft., From . ft. to . ft.					
6 GROUT MATERIAL:					
☐ 1 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other					
Grout intervals: From 3 ft. to 23 ft., From . ft. to . ft., From . ft. to . ft.					
What is the nearest source of possible contamination:					
☐ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well					
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well					
☒ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)					
☐ 13 Insecticide storage					
Direction from well? North How many feet? 75					
FROM		TO		LITHOLOGIC LOG	
FROM		TO		PLUGGING INTERVALS	
0	3	top soil			
3	18	clay			
18	25	Med sand			
25	50	Red shale			
50	123	Blue shale			
123	130	Red shale			
130	136	Blue shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-22-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 11-25-91 under the business name of Weninger Drilling Inc. by (signature) [Signature]					