


1 LOCATION OF WATER WELL: Fraction NW 1/4 SE 1/4 SW 1/4 Section Number 24 Township Number T 27 S Range Number R 2 E W

County: Levy Distance and direction from nearest town or city street address of well if located within city?

See Below

2 WATER WELL OWNER: SCOTT MASTERSON
RR#, St. Address, Box #: 411 FORESTVIEW
City, State, ZIP Code: WICHITA KS 67212
Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 18 ft. 2. 18 ft. 3. 18 ft.

WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 6-17-94

Pump test data: Well water was 18 ft. after 20 hours pumping 20 gpm

Est. Yield 40 gpm: Well water was 18 ft. after 20 hours pumping 20 gpm

Bore Hole Diameter 11 in. to 50 ft. and 50 in. to 50 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded

2 PVC 4 ABS 7 Fiberglass Threaded

Blank casing diameter 5 in. to 40 ft. Dia. 40 in. to 40 ft. Dia. 40 in. to 40 ft. Dia. 40 in. to 40 ft. Dia.

Casing height above land surface 12 in. weight 2.60 lbs./ft. Wall thickness or gauge No. 160 PVC

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 5 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 40 ft. to 50 ft. From 40 ft. to 50 ft. From 40 ft. to 50 ft. From 40 ft. to 50 ft.

From 18 ft. to 50 ft. From 18 ft. to 50 ft. From 18 ft. to 50 ft. From 18 ft. to 50 ft.

GRAVEL PACK INTERVALS: From 18 ft. to 50 ft. From 18 ft. to 50 ft. From 18 ft. to 50 ft. From 18 ft. to 50 ft.

From 18 ft. to 50 ft. From 18 ft. to 50 ft. From 18 ft. to 50 ft. From 18 ft. to 50 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 18 ft. From 3 ft. to 18 ft. From 3 ft. to 18 ft. From 3 ft. to 18 ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? EAST How many feet? 40

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 2 Top soil

2 17 Clay

17 32 fine sand

32 33 Clay

33 50 gravel