


1 LOCATION OF WATER WELL: County: Edgewick Fraction: SE 1/4 NE 1/4 SE 1/4 Section Number: 25 Township Number: T 27 S Range Number: R 2 W
 Distance and direction from nearest town or city street address of well if located within city? See Below.

2 WATER WELL OWNER: ROGER MOSSIE
 RR#, St. Address, Box #: 1401 So 119th W. Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: WICHITA KS 67235 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION: 9-25-90
 Depth(s) Groundwater Encountered 1. 29 ft. 2. 29 ft. 3. 20 ft.
 WELL'S STATIC WATER LEVEL 29 ft. below land surface measured on mo/day/yr 9-25-90
 Pump test data: Well water was 29 ft. after 12 hours pumping 20 gpm
 Est. Yield 50 gpm: Well water was 29 ft. after 12 hours pumping 20 gpm
 Bore Hole Diameter 11 in. to 100 ft. and 100 in. to 100 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 8 Air conditioning ☐ 11 Injection well
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 9 Dewatering ☐ 12 Other (Specify below)
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
☒ 1 Steel ☐ 3 RMP (SR) ☐ 6 Asbestos-Cement ☐ 8 Concrete tile ☐ CASING JOINTS: Glued X Clamped X
☒ 2 PVC ☐ 4 ABS ☐ 7 Fiberglass ☐ 9 Other (specify below) ☐ Welded ☐ Threaded
 Blank casing diameter 5 in. to 1280 ft. Dia 2.59 in. to 100 ft. Dia 100 in. to 100 ft.
 Casing height above land surface 1280 in. weight 2.59 lbs./ft. Wall thickness or gauge No. SPR-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 8 RMP (SR) ☐ 10 Asbestos-cement
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 11 Other (specify)
☐ 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes
☐ 7 Torch cut ☐ 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 80 ft. to 100 ft. From 80 ft. to 100 ft.
 GRAVEL PACK INTERVALS: From 23 ft. to 100 ft. From 23 ft. to 100 ft.

6 GROUT MATERIAL: ☐ 1 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other
 Grout Intervals: From 3 ft. to 23 ft. From 3 ft. to 23 ft. From 3 ft. to 23 ft. From 3 ft. to 23 ft.
 What is the nearest source of possible contamination:
☐ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☒ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage
 Direction from well? South. How many feet? 15

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soil			
2	23	clay			
23	46	fine sand.			
46	71	clay			
71	79	fine sand.			
79	80	clay			
80	100	med. sand.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-25-90 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 31825 This Water Well Record was completed on (mo/day/yr) 10-2-90
 under the business name of Wenger Dully by (signature) Roger Mossie