

1 LOCATION OF WATER WELL: County: Sedgwick Distance and direction from nearest town or city street address of well if located within city? 15335 Lynndale Wichita, KS		Fraction NW 1/4 SE 1/4 SE 1/4	Section Number 27	Township Number T 27 S	Range Number R 2 E
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Tony Strunk 2600 So. 183rd West Goddard, Ks. 67052			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 80 ft.			
		Depth(s) Groundwater Encountered 1. 38 ft. 2. 38 ft. 3. 5-12-88 ft. WELL'S STATIC WATER LEVEL 38 ft. below land surface measured on mo/day/yr Pump test data: Well water was 45 ft. after 12 hours pumping 20 gpm Est. Yield 25 gpm: Well water was 45 ft. after 12 hours pumping 20 gpm Bore Hole Diameter 11 in. to 80 ft., and . in. to . in. to . ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes.....No..... If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 HMP (SR) 4 ABS Blank casing diameter . in. to . ft., Dia . in. to . ft., Dia . in. to . ft. Casing height above land surface . in., weight . lbs./ft. Wall thickness or gauge No. SDR-26		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued Clamped Welded Threaded.			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 HMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)		SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 11 None (open hole) SCREEN-PERFORATED INTERVALS: From . ft. to . ft., From . ft. to . ft., From . ft. to . ft. GRAVEL PACK INTERVALS: From . ft. to . ft., From . ft. to . ft., From . ft. to . ft.			
6 GROUT MATERIAL: Neat cement Cement Grout 3 Bentonite 4 Other Grout Intervals: From . ft. to . ft., From . ft. to . ft., From . ft. to . ft.		What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Direction from well? South How many feet? 80			
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0 2 Topsoil					
2 34 Clay					
34 80 Charcoal Shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-12-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 6-29-88 under the business name of Weninger Drilling by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					