


1 LOCATION OF WATER WELL: Fraction SW 1/4 NE NE 1/4 Section Number 17 Township Number T 27 S Range Number R 2  
 County: Sedgwick  
 Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: See Below  
 RR#, St. Address, Box # 1240 W. 199th Cr.  
 City, State, ZIP Code Conway, KS 67030  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITHIN AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL 96 ft. ELEVATION: 9/16/94

Depth(s) Groundwater Encountered 32 ft. 2. 30 ft. 3. 12 ft.

WELL'S STATIC WATER LEVEL 32 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 25 gpm Well water was 96 ft. after 12 hours pumping gpm

Est. Yield 25 gpm Well water was 96 ft. after 12 hours pumping gpm

Bore Hole Diameter 11 in. to 96 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded

2 PVC 5 ABS 7 Fiberglass Threaded

Blank casing diameter 5 in. to 34 ft. Dia in. to ft. Dia in. to ft.

Casing height above land surface 12 in. weight 2.60 lbs./ft. Wall thickness or gauge No. 1.60 PSI

TYPE OF SCREEN OR PERFORATION MATERIAL: 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 34 ft. to 96 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 32 ft. to 96 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 3 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 32 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? Northeast How many feet? 180

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 2 Top Soil

2 35 clay

35 96 shale

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was

completed on 9/20/94 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 318 This Water Well Record was completed on 10-3-94

under the business name of Weninger Drilling by (signature) Karrina Marissey