

1	LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County:	Sedgwick	SE $\frac{1}{4}$ NE $\frac{1}{4}$ SE $\frac{1}{4}$	24	T 27 S	R 2 E
Distance and direction from nearest town or city street address of well if located within city?					

2 WATER WELL OWNER: Wayne Largent
RR#, St. Address, Box # 12030 W. Merribeau Ct.
City, State, ZIP Code Wichita, KS 67235 105

Board of Agriculture, Division of Water Resources
Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

DEPTH OF COMPLETED WELL: _____ ft. ELEVATION: _____ ft.

Depth(s) Groundwater Encountered _____ ft. 2. _____ ft. 3. _____ ft.

WELL'S STATIC WATER LEVEL _____ ft. below land surface measured on mo/day/yr _____ 12/12/94

Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm

Est. Yield _____ gpm: Well water was _____ ft. after _____ hours pumping _____ gpm

Bore Hole Diameter _____ in. to _____ ft. and _____ in. to _____ ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	9 Dewatering
	7 Lawn and garden only	12 Other (Specify below)
	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes _____ No X If yes, mo/day/yr sample was submitted _____

Water Well Disinfected? Yes X No _____

5 TYPE OF BLANK CASING USED:		6 Wrought iron		8 Concrete tile		CASING JOINTS: Glued ☒ Clamped ☐	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)			Welded	
2 PVC	4 ABS	7 Fiberglass				Threaded	
Blank casing diameter 5 in. to 12.45 ft. Dia		in. to .ft. Dia		in. to .ft. Dia		in. to 140 PVC ft.	
Casing weight above land surface 2.60 lbs./ft.		Weight		Wall thickness or gauge No.		140 PVC	
TYPE OF SCREEN OR PERFORATION MATERIAL							
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement			
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)			
			9 ABS	12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)			
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes				
		7 Torch cut	10 Other (specify)				
SCREEN-PERFORATED INTERVALS: From .ft. to .ft. From .ft. to .ft.							
GRAVEL PACK INTERVALS: From 45 ft. to 65 ft. From .ft. to .ft.							

6] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3 ft. to 42 ft. From ft. to ft. From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? North How many feet? 20

Direction from well?		LITHOLOGIC LOG	How many feet?	
FROM	TO		FROM	TO
				PLUGGING INTERVALS
0	2	Top Soil		
2	32	Clay		
32	38	fine sand		
38	65	Sand		

7. CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/13/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 12-14-94 under the business name of Weninger Drilling by (signature) Kayana Morrison