


USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD  
KSA 82a-1201-1215

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health  
(Water Well Contractors)  
Forbes-Bldg. 740  
Topeka, Kansas 66620

1 Location of well:	County <b>Kiowa</b>	Township name <b>Martin</b>	Fraction <b>CNE 1/4</b>	Section number <b>31</b>	Town number <b>T27S</b>	Range number <b>R20W</b>				
Distance and direction from nearest town or city: <b>7 1/2 mi. Northwest of Mullenville, KS</b> Street address of well location if in city:				3 Owner of well: <b>Don Broomfield</b> Address: <b>Augusta, Kansas</b>						
Locate with "X" in section below: N 		Sketch map:		4 Well depth: <u>116</u> ft. Date of completion <u>8-21-75</u> Well diameter <u>24</u> in.						
SEE RECORD BELOW				5 <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary						
				6 Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Commercial <input type="checkbox"/> Test well						
2 Type and color of material				7 Casing: Material <u>Steel</u> Height: <u>above</u> below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface <u>12</u> in. Diam. Weight <u>30.3</u> lbs./ft. ___ in. to ___ ft. depth Drive shoe? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No ___ in. to ___ ft. depth						
				8 Screen: Manufacturer <u>SEE RECORD BELOW</u> Type ___ Dia. <u>16"</u> <u>Slot</u> gauge <u>1/8</u> Length <u>41'</u> Set between ___ ft. and ___ ft. Fittings: <u>3/8"</u> Gravel pack <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Size range of material ___						
Sand				9 Static water level: <u>34</u> ft. below land surface Date <u>8-21-75</u>						
Sand & gravel				10 Pumping level below land surfaces: <u>N/C</u> ___ ft. after ___ hrs. pumping ___ g.p.m. ___ ft. after ___ hrs. pumping ___ g.p.m. Estimated maximum yield ___ g.p.m.						
Blue & brown clay & limestone streaks				11 Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date ___						
Brown clay, lime streaks & gravel streaks				12 Well head completion: <input type="checkbox"/> Pitless adapter <u>12</u> inches above grade						
Sand & gravel				13 Well grouted? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Depth: From <u>0</u> ft. to <u>10</u> ft.						
Brown clay & limestone streaks				14 Nearest source of possible contamination: ft. ___ Direction ___ Type ___ Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No						
CASING & SCREEN RECORD				15 Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name ___ Model number ___ HP ___ Volts ___ Length of drop pipe ___ ft. capacity ___ g.m.p. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other						
				16" - 7 ga. Plain casing				16 Remarks: elevation		
				16" - .125 Irr. Johnson screen				Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley		
				16" - 7 ga. Plain casing				17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <b>Clarke Well &amp; Eq., Inc.</b> <u>185</u> Business name License No. Address <u>Great Bend, KS</u> Signed <u>[Signature]</u> Date <u>8-21-75</u> Authorized representative		
				16" - double-slot Doerr screen						
16" - .125 Irr. Johnson screen										
16" - 7 ga. Plain casing										
(use a second sheet if needed)										