


1 LOCATION OF WATER WELL: County: <u>Kiowa</u>	Fraction <u>1/4 NC 1/4 NE 1/4</u>	Section Number <u>23</u>	Township Number <u>T 27 S</u>	Range Number <u>R 20 E/W</u>
---	--------------------------------------	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?
6 North of Mullinville, Ks.

2 WATER WELL OWNER: Russell ~~FRANK~~ Fralick
 RR#, St. Address, Box # : Box 66 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Mullinville, Ks. 67109 Application Number: 3157

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL <u>104</u> ft. ELEVATION: Depth(s) Groundwater Encountered, 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>48</u> ft. below land surface measured on mo/day/yr <u>12-23-03</u> Pump test data: Well water was <u>62</u> ft. after <u>2</u> hours pumping <u>900</u> gpm Est. Yield <u>1000</u> gpm; Well water was <u>63</u> ft. after <u>2 1/2</u> hours pumping <u>1000</u> gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u>; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>HTH</u> No
---	--

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded

Blank casing diameter 16 in. to 64 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 24 in., weight Sch 40 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)
 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.

SCREEN-PERFORATED INTERVALS: From 104 ft. to 64 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 104 ft. to 20 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug
 Grout intervals: From 20 ft. to 0 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage None

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	SANDY TOP SOIL Sandy top soil			
3	12	Gray clay			
12	28	Sand & gravel med, loose, with clay pieces			
28	79	Sand & gravel med, coarse, loose			
79	87	Tan clay			
87	97	Sand & gravel med, loose			
97	104	Tan & white clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) ~~XXXXXX~~ 1-20-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 134 This Water Well Record was completed on (mo/day/yr) 1-27-04 under the business name of Rosencrantz - Bemis by (signature) John Albre