

1 LOCATION OF WATER WELL:	Fraction	SW 1/4	SW 1/4	SW 1/4	Section Number	32	Township Number	T 27 S	Range Number	R 21 EW
---------------------------	----------	--------	--------	--------	----------------	----	-----------------	--------	--------------	---------

Distance and direction from nearest town or city street address of well if located within city?
6 North of Bucklin, Kansas

2 WATER WELL OWNER:	Mr. Rob Sellard	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Route 2	Application Number: ---
City, State, ZIP Code :	Bucklin, Kansas 67834	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: Slope
	Depth(s) Groundwater Encountered 1. Not available ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ... 22 ft. below land surface measured on mo/day/yr June 18, 1987. Pump test data: Well water was ft. after hours pumping gpm Est. Yield .15 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter .10 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No XX; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XX No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued XX Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
XX PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 20 ft., Dia			Threaded
Casing height above land surface 20 in., weight 2.8 lbs./ft. Wall thickness or gauge No. 265			
TYPE OF SCREEN OR PERFORATION MATERIAL:	XX PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	XX Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 20 ft. to 40 ft.		
GRAVEL PACK INTERVALS:	From 20 ft. to 40 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	XX Other Baroid Hole Plug
Grout Intervals:	From 0 ft. to 20 ft.			
What is the nearest source of possible contamination:	XX Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well?	North	How many feet?	1000	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Topsoil			
2	0	Fine Sand			
8	28	Med. Gravel			
28	30	Clay			
30	40	Fine Sand & Gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:	This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) June 19, 1987 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/yr) June 26, 1987 under the business name of FRIESEN WINDMILL & SUPPLY INC. by (signature)
--	---

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

8910000078-20